



D-shackle

TECHNICAL DATA : -

1. BALL & SOCKET DESIGNATION - 20 MM. AS PER IS: 2486
2. GALVANIZING WILL CONFORM TO IS: 2629 & IS: 2633
 ZINC COATING THICKNESS - 610 GM./SQ.MTR. FOR UNTHREADED PART & 305 GM/SQ.MTR FOR THREADED PART,
 UNIFORMITY OF COATING - 4 DIPS OF 1 MIN.
3. HARDWARE FITTINGS WILL CONFORM TO DRG.
4. SLIP STRENGTH OF TENSION CLAMP - 95% OF THE UTS OF CONDUCTOR
5. ALL FERROUS PARTS ARE HOT DIP GALVANISED
 EXCEPT SPRING WASHER ELECTRO GALVANISED (IS-1573).
6. SECURITY CLIP SHALL BE MADE OF STAINLESS STEEL ('R' TYPE)
7. UTS OF HARDWARE FITTINGS - 160 KN.

Drawing for tender call notice
 NO. EHT(G)/T/02/2018-19

TECHNICAL DETAILS:

1. ALL DIMENSION ARE IN MM.
2. GENERAL TOLERANCE $\pm 5\%$ OR AS SPECIFIED.
3. DRAWING NOT TO SCALE

SR.NO	DESCRIPTION	MATERIAL/GRADE	SURFACE TREATMENT	QTY
2	BOLT & NUT	MILD STEEL	H.D.G	1+1
1	HANGER	MILD STEEL	H.D.G	1

- TECHNICAL DATA :-**
1. BALL & SOCKET DESIGNATION - 20 MM, AS PER IS: 2486
 2. GALVANIZING WILL CONFORM TO IS: 2629 & IS: 2633
 3. ZINC COATING THICKNESS - 610 GM./SQ.MTR. FOR UNTHREADED PART & 305 GM./SQ.MTR FOR THREADED PART.
 4. UNIFORMITY OF COATING - 4 DIPS OF 1 MIN.
 5. HARDWARE FITTINGS WILL CONFORM TO DRG.
 6. SLIP STRENGTH OF TENSION CLAMP - 95% OF THE UTS OF CONDUCTOR
 7. ALL FERROUS PARTS ARE HOT DIP GALVANISED EXCEPT SPRING WASHER ELECTRO GALVANISED (IS-1573).
 8. SECURITY CLIP SHALL BE MADE OF STAINLESS STEEL ('R' TYPE)
 9. UTS OF HARDWARE FITTINGS - 160 KN (120 KN)

HANGER 20 MM

TITLE:

Drawing for tender Call Notice
 No. EHTC/T/02/2018-19

