

ODISHA POWER TRANSMISSION CORPORATION LIMITED

OFFICE OF THE SENIOR GENERAL MANAGER CENTRAL PROCUREMENT CELL JANAPATH, BHUBANESWAR-751022

TEL NO- 0674-2541801 FAX NO: 0674-2542964
TENDER SPECIFICATION NO
SR.G.M-C.P.C- e TENDER-HARD WARE FITTINGS & ACCESSORIES27/2024-25 FOR

PROCUREMENT OF HARD WARE FITTINGS & ACCESSORIES FOR DIFFERENT TYPES OF CONDUCTOR

PART-I COMMERCIALBID

SECTION-I INSTRUCTION TO TENDERERS

SECTION-II GENERAL CONDITIONS OF CONTRACT

SECTION-III LIST OF ANNEXURES

SECTION-IV TECHNICAL SPECIFICATION

PART-II PRICEBID

Request for online tender	From	Date	11.04.2025	То	Date	02.05.2025
documents		Time	11.00Hrs		Time	12:30Hrs
Last date of submission of online tender					Date	02.05.2025
				Time	13:00Hrs	
Date of opening of Tender				Date	03.05.2025	
					Time	11.00Hrs



ODISHA POWER TRANSMISSION CORPORATION LTD.

REGD. OFFICE: JANPATH, BHUBANESWAR - 751 022, ODISHA

e-TENDER NOTICE NO.CPC- 27/2024-25

For and on behalf of ODISHA POWER TRANSMISSION CORPORATION LTD, Sr.G.M. (CPC) invites Tenders from reputed manufacturers in two part bidding system for supply of **Hard Ware Fittings & Accessories for Different Types of Conductor**. The interested bidders would be required to enroll themselves on the tender portal www.tenderwizard.com/OPTCL. Complete set of bidding documents are available at www.tenderwizard.com/OPTCL from 11.04.2025 (11.00 Hrs) up to 02.05.2025 (13.00Hrs). Interested manufacturers may visit OPTCL's official web site http://www.optcl.co.in and www.tenderwizard.com/OPTCL for detail specification.

N.B:- All subsequent addendums/corrigendum to the tender shall be hosted in the OPTCL's official web site http://www.optcl.co.in and www.tenderwizard.com/OPTCL only.

SENIOR GENERAL MANAGER (CPC)



NOTICE INVITING e-TENDER

ODISHA POWER TRANSMISSION CORPORATION LTD., REGD. OFFICE: JANPATH, BHUBANESWAR - 751022, ODISHA, INDIA.

e-TENDER NOTICE NO.CPC- 27/2024-25

For and on behalf of the ODISHA POWER TRANSMISSION CORPORATION LTD, the undersigned invites bids under two-part bidding system in e- tendering mode only as per the following details.

Tender	Description	INI	Last Date of		
Specification No.	of material and Quantity Required	Earnest Money Deposit	Cost of Tender Docume nt	Tender Processin g fee	submission & Date of opening of Tender
Sr.G.M-CPC-e Tender-Hard Ware Fittings & Accessories- 27/ 2024-25	As per Table-A below	Rs.4,74,587.	Rs 12,000/- (+) Rs 2,160/- (@ 18% GST) = 14,160/-	Rs.5,900/- (Including GST @ 18%)	Last Date of submission- 02.05.2025(1 3.00Hrs) Date of opening of Tender- 03.05.2025 (11.00Hrs)

TABLE-A:

	Description	Unit	Quantity
	(1.1) 90KN Single Suspension (AGS Type) H/W fitting including armour rod for ACSR Panther conductor	Sets	4744
Hard Ware Fittings for ACSR Panther (30+7/3.00mm)	(1.2) 90KN Double Suspension (AGS Type) H/W fitting including armour rod for ACSR Panther conductor	Sets	582
	(1.3) 120KN Single Tension H/W fitting for ACSR Panther conductor	Sets	3128
	(1.4) 120KN Double Tension H/W fitting for ACSR Panther conductor	Sets	1172
Hard Ware Fittings for ACSR Zebra (54+7/3.18mm)	(1.5) 120KN Single Suspension H/W fitting including armour rod (AGS Type) for ACSR Zebra conductor	Sets	291
	(1.6) 120KN Doule Suspension H/W fitting including armour rod (AGS Type) for ACSR Zebra conductor	Sets	124
	(1.7) 160KN Single Tension H/W fitting for ACSR Zebra conductor	Sets	1528
	(1.8) 160KN Double Tension H/W fitting for ACSR Zebra conductor	Sets	392

Hard Ware Fittings for ACSR Moose	(1.9) 120KN Single Suspension (AGS Type) H/W fitting including armour rod for ACSR Moose	Sets	324
(54+7/3.53mm)	conductor	0 .	500
	(1.10) 160KN Single Tension H/W fitting for ACSR	Sets	583
	Moose conductor	0.4	205
	(1.11) 160KN Double Tension H/W fitting for ACSR	Sets	305
II1 XV Ditti	Moose conductor	O-4-	20
Hard Ware Fittings for AAAC Zebra	(1.12) 120KN Single Suspension H/W fitting	Sets	20
	including armour rod (AGS Type) for AAAC Zebra		
(37/4.0mm)	conductor	O-4-	00
	(1.13) 120KN Doule Suspension H/W fitting	Sets	98
	including armour rod (AGS Type) for AAAC Zebra		
Hand Wana Ditting	conductor	0-4-	26
Hard Ware Fittings	(1.14) 90KN Single Suspension H/W fitting	Sets	36
for AAAC Panther	including armour rod (AGS Type) for AAAC Panther		
	conductor	0.4	1.6
	(1.15) 120KN Single Tension H/W fitting for AAAC	Sets	46
	Panther conductor		1.5
Hard Ware Fittings	(1.16) 120KN Double Suspension (AGS Type) H/W	Sets	16
for AAAC Moose	fitting including armour rod for ACSR Moose		
	conductor		
Hard Ware Fittings	(1.17) Single Tension H/W fitting for Earth Wire	Sets	79
for Earthwire	(0.4) + 0.00 p1	1	1.5000
Vibrataion Damper	(2.1) ACSR Panther conductor	Nos.	15022
	(2.2) AAAC Panther conductor	Nos.	262
	(2.3) ACSR Moose conductor	Nos.	167
Mid Span Joint	(3.1) ACSR Zebra	Nos.	47
-	(3.2) ACSR Panther	Nos.	947
	(3.3) ACSR Moose	Nos.	29
Repair Sleeve	(4.1) ACSR Panther	Nos.	275

The bidders can view the tender documents from website free of cost.

TENDER COST:

The bidders who want to submit bids shall have to pay non-refundable amount 14,160/- only including GST @ 18%) towards the tender cost, online through e-payment gateway link provided in e-tender portal (by using Net Banking, Debit Card or Credit Card). The online payment can be made prior to last date & time of submission of online tender. They have to also submit notarized hard copy of GST registration certificate on or before the scheduled date & time of opening of techno-commercial bid. They have to also submit notarized hard copy of GST registration certificate on or before the date & time of submission of techno-commercial bid.

TENDER PROCESSING FEE:

The bidders shall have to submit non-refundable amount of Rs.5,900/-(Rupees Five thousand & nine hundred) only including GST @ 18%) towards the tender processing fee to K.S.E.D.C.Ltd, in e-payment mode. The e-payment of above amount is to be made to enable the bidder to down load the bid proposal sheets & bid document in electronic mode.

SUBMISSION OF TENDER COST, TENDER PROCESSING FEE & EMD:

The bidder shall deposit the tender cost, tender processing fee & EMD BG prior to last date & time for submission of bid as notified in tender notice. Local micro & small enterprisers (MSEs) (In the state of Odisha) based in Odisha and registered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC can participate by submitting EMD @ 50(fifty) percent(%) of the amount indicated in the Notice Inviting Tender. They have to submit notarized hard copy of valid registration as local MSE (In the state of Odisha) as above on or before the date & time of submission of techno-commercial bid.

The tender cost, processing fees are to be submitted along with the EMD at the office of the undersigned on or before the last date & time of submission of tender.

The bidders shall scan the Demand Draft/Pay order/ Bank guarantee, towards EMD/ notarised hard copy of valid registration as local MSE (In the state of Odisha) (if any) and upload the same in the prescribed form in .gif or .jpg format in addition to sending the original as stated above.

The prospective bidders are advised to register their user ID, Password, company ID from website **www.tenderwizard.com/OPTCL** by clicking on hyper link "Register Me".

Any clarifications regarding the scope of work and technical features of the tender can be had from the undersigned during office hours.

Minimum qualification criteria of bidders: AS STIPULATED IN SECTION-II, (G.T.C.C) OF THE TENDER SPECIFICATION.

SENIOR GENERAL MANAGER, CENTRAL PROCUREMENT CELL



FAX NO.: 0674 - 2542964

TELEPHONE NO: 0674 – 2541801

ODISHA POWER TRANSMISSION CORPORATION LTD.

CENTRAL PROCUREMENT CELL

JANAPATH, BHUBANESWAR – 751022

TENDER SPECIFICATION NO-Sr.G.M-CPC-III-e TENDER-HARDWARE FITTINGS & ACCESSORIES-27/2024-25

CONTAINING

<u>PART – I</u>

SECTION – I : INSTRUCTION TO TENDERERS

SECTION – II : GENERAL TERMS AND CONDITIONS OF CONTRACT (G.T.C.C.)

(COMMERCIAL)

SECTION – III: LIST OF ANNEXURES (COMMERCIAL)

SECTION – IV: TECHNICAL SPECIFICATION

PART – II PRICE BID.

TABLE OF CONTENTS

PART - I.

SECTION - I.

INSTRUCTIONS TO TENDERERS

Clause.	<u>Title.</u> <u>Page.</u>	
1.	Submission of Bids.	02
2.	Division of Specification.	02
3.	Tenders shall be in two parts.	
4.	Opening of Bids .	03
5.	Purchaser's right regarding alteration in	04
	Quantities, Tendered.	
6.	Procedure and opening time of tenders.	04
7.	Bidder's liberty to deviate from specification.	
8.	Eligibility for submission of bids.	04
9.	Purchaser's right to accept/reject bids.	10
10.	Mode of submission of tenders.	10
11.	Earnest money deposit.	10
12.	Validity of the bids.	11
13.	Price.	11
14.	Revision of Tender Price by Bidders.	11
15.	Tenderers to be fully conversant with	11
	the clauses of the Specification.	
16.	Documents to accompany Bids.	11
17.	Documents/Papers to Accompany PART - II Bid.	12
18.	Conditional Offer.	12
19.	General.	12
20.	Expenses in respect of OPTCL"s representative	14
	for witnessing the inspection & testing of	
	the offered Equipment/materials at the	
	inspection and testing site.	
21.	Litigation/ Arbitration	16

COMMERCIAL SPECIFICATION.

PART-I

SECTION-I

INSTRUCTIONS TO TENDERER

1. Submission of Bids:-

The bidder shall submit the bid in Electronic Mode only i.e www.tenderwizard.com/OPTCL. The bidder must ensure that the bids are received in the specified website of the OPTCL by the date and time indicated in the Tender notice. Bids submitted by telex/telegram will not be accepted. No request from any bidder to the OPTCL to collect the Bids in physical form will be entertained by the OPTCL.

The OPTCL reserves the right to reject any bid, which is not deposited according to the instruction, stipulated above. The participants to the tender should be registered under GST Laws.

- 1. For all the users it is mandatory to procure the Digital Signatures of Class-III.
- **2.** Contractors / Vendors / Bidders / Suppliers are requested to follow the below steps for Registration:
 - (a) Click "Register", fill the online registration form.
 - (b) Pay the amount of Rs. 2360/- through e-payment in favour of K S E D C Ltd Payable at Bangalore.
 - (c) Send the acknowledgment copy for verification.
 - (d) As soon as the verification is being done the e-tender user id will be enabled.
- **3.** After viewing Tender Notification, if bidder intends to participate in tender, he has to use his e-tendering User Id and Password which has been received after registration and acquisition of DSCs.
- **4.** If any Bidder wants to participate in the tender he will have to follow the instructions given below:
 - (a) Insert the PKI (which consist of your Digital Signature Certificate) in your System.
 - (Note: Make sure that necessary software of PKI be installed in your system).
 - (b) Click / Double Click to open the Microsoft Internet Explorer (This icon will be located on the Desktop of the computer).
 - (c) Go to Start > Programs > Internet Explorer.
 - (d) Type **www.tenderwizard.com/OPTCL**in the address bar, to access the Login Screen.
 - (e) Enter e-tender User Id and Password, click on "Go".
 - (f) Click on "Click here to login" for selecting the Digital Signature Certificate.
 - (g) Select the Certificate and enter DSC Password.
 - (h) Re-enter the e-Procurement User Id Password

- **5.** To make a request for Tender Document Bidders will have to follow below mentioned steps.
 - Click "Un Applied" to view / apply for new tenders.
 - Click on Request icon for online request.
- **6.** After making the request Bidders will receive the Tender Documents which can be checked and downloaded by following the below steps:
 - Click to view the tender documents which are received by the user.
 - Tender document screen appears.
 - Click "Click here to download" to download the documents.
- **7.** After completing all the formalities Bidders will have to submit the tender and they must take care of following instructions.
 - Prior to submission, verify whether all the required documents have been attached and uploaded to the particular tender or not.
 - Note down / take a print of bid control number once it displayed on the screen
- 8. Tender Opening event can be viewed online.
- 9. Competitors bid sheets are available in the website for all.

10. For any e-tendering assistant contact help desk number mentioned below.

• Bangalore – 080- 40482000.

The participants to the tender should be registered under GST Laws.

2. Division of Specification.

The specification is mainly divided into two parts viz. Part-I & Part-II.

Part-I Consists of

[i] Section-I Instruction to Tenderers.

[ii] Section-II General Terms & conditions of contract.

[iii] Section-III Schedules and forms etc. [iv] Section-IV Technical Specification.

Part-II Consists of

Schedule of prices as per Annexure-V.

3. Tenders shall be in Two Parts.

The Tenderers are required to submit the tenders in two parts viz. Part-I (Techno commercial) & Part-II (Price bid).

The Tenderers are required to submit the tenders in two parts Part-I, technical and commercial and Part-II "Price Bid".

4. Opening of Bids.

[a] The part-I shall be opened on the date and time fixed by the OPTCL for opening of bids in Electronic mode in presence of such of the Tenderers or their authorized representatives [limited to one person only] on the due date of opening of tender who opt remain present. After scrutiny of the technical particulars and other commercial terms, clarifications, if required, shall be sought for from the bidders. The Tenderers shall be allowed 15 days time for such activity.

[b] On receipt of technical clarification, the bids shall be reviewed, evaluated and those not in conformity with the technical Specification / qualifying experience, shall be rejected. If any of the technical proposal requires modification to make them comparable, discussion will be held with the participating bidders.

All the responsive bidders shall be given opportunity to submit the revised technical and revised price proposals as a follow up to the clarification (modification if any) on the technical proposals. The qualified bidders shall be given opportunity to submit revised price proposals within 15 days from the date of such discussion or within time frame mutually agreed, whichever is earlier.

- [c] When the revised price proposals are received, the original price proposals will be returned to the bidders unopened along with their original technical proposals. Only the revised technical and price proposals will be considered for bid evaluation. The price bids [Part-II] of such of the Tenderers, whose tenders have been found to be technically and commercially acceptable, including those supplementary revised price bids, submitted subsequently, shall be opened in the presence of the bidder's representative on a date and time which will be intimated to all technically and commercially acceptable Tenderers.
- [d] The bidders are required to furnish sufficient information to the Purchaser to establish their qualification, capacity to manufacture and/or supply the materials/perform the work. Such information shall include details of bidder's experience, its financial, managerial and technical capabilities.
- [e] The bidders are also required to furnish details of availability of appropriate technical staff and capability to perform after sales services. The above information shall be considered during scrutiny and evaluation of bids and any bid which does not satisfactorily meet these requirements, shall not be considered for price bid evaluation.
- [f] The price bids of the technically and otherwise acceptable bids shall only be evaluated as per the norms applicable in terms of this Specification.

5. Purchaser's Right Regarding Alteration of Quantities Tendered.

The Purchaser may alter the quantities of materials/equipment at the time of placing orders. Initially the purchaser may place orders for lesser quantity with full freedom to place extension orders for further quantity under similar terms and conditions of the original orders. Orders may also be split among more than one tenderer for any particular item, if considered necessary in the interest of the Purchaser to get the goods/equipment earlier.

6. Procedure and opening time of tenders.

Tenders will be opened in the office of the Senior General Manager [C.P.C.] on the specified date and time in presence of the Tenderers or their authorized representatives [limited to one person only] in case of each bidder who may desire to be present, at the time of opening the bids.

7. <u>Bidder's Liberty to deviate from Specification.</u>

The Tenderer may deviate from the specification while quoting, if in his opinion, such deviation is in line with the manufacturer's standard practice and conducive to a better and more economical offer. All such deviations should however be clearly

indicated giving full justifications for such deviation. [Read with Clause-9, Section-II of the Specification].

8. Eligibility for submission of bids.

Only those manufacturers who have deposited the cost of tender specification are eligible to participate in the tender. They should submit the money receipt as a proof of such payment. The local Micro and small Enterprises(MSEs)(In the state of Odisha) based in Odisha and registered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC can participate without payment of the cost of tender specification.

9. Purchaser's right to accept/reject bids:

The purchaser reserves the right to reject any or all the tenders without assigning any reasons what so ever if it is in the interest of OPTCL, under the existing circumstances. [Read with clause-10, Section-II of the specification].

10. Mode of submission of Tenders.

- [A] Tenders shall be submitted in electronic mode only. (www.tenderwizard.com/OPTCL)
- [B] **Telegraphic or FAX tenders** shall not be accepted under any circumstances.

11. Earnest money deposit:

The tender shall be accompanied by Earnest Money deposit of value specified in the notice inviting tenders against each lot / bid. Tenders without the required EMD as indicated at **Annexure-VIII** will be rejected out rightly.

The local Micro and small Enterprises(MSEs)(In the state of Odisha) based in Odisha and registered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC can participate by submitting Earnest Money Deposit @ fifty percent of the amount indicated in the Notice Inviting Tender.

The earnest money deposit shall be furnished in one of the following forms subject to the conditions mentioned below:

- (a) **Bank Draft**: -To be drawn in favour of Drawing & Disbursing Officer, OPTCL [H.Qrs.Office], Bhubaneswar-751 022.
- (b) Bank Guarantee from any Nationalized/Scheduled Bank strictly as per enclosed proforma vide **Annexure-VI** to be executed on non-judicial stamp paper worth Rs.29.00 or as applicable, as per prevailing laws in force and also to be accompanied by the confirmation letter of the issuing Bank Branch.

NOTE:

- (i). The validity of the EMD in the form of Bank Guarantee shall be at least for 240 days from the date of opening of tender failing which the tender will be liable for rejection.
- (ii) No interest shall be paid on the Earnest Money Deposit.

- (iii) E.M.D. in shape of cash may be submitted up to Rs. 25,000/- (Rupees Twenty-five) Thousand) only. Above Rs. 25,000/- (Rupees Twenty-five thousand) the Earnest Money Deposit shall be furnished in any one of the forms indicated above (i.e. Through Bank Draft, Bank Guarantee/ National Savings Certificate).
- (iv) No adjustment towards EMD shall be permitted against any outstanding amount with the **ODISHA POWER TRANSMISSION CORPORATION LTD**.
- (v) The chart showing particulars of EMD to be furnished by Tenderers of different categories is placed at **Annexure-VIII.**
- (vi) In the case of un- successful tenderer, the EMD will be refunded after the tender is decided. In the case of successful Tenderer, this will be refunded only after furnishing of security money referred to at <u>clause-19 of Section-II</u>.
- (vii) Suits, if any, arising out of this clause shall be filed in a Court of law to which the jurisdiction of High Court of ODISHA extends.
- (vii) EMD will be forfeited if the tenderer fails to accept the letter of intent and/or purchase order issued in his favour or to execute the order, placed on them.
- (viii) Tenders not accompanied by Earnest Money shall be disqualified.

12. Validity of the Bids: -

The tenders should be kept valid for a period of **180** days from the date of opening of the tender, failing which the tenders will be rejected.

13. PRICE: -

i) Tenderers are requested to quote-'FIRM' Price. No deviation from **FIRM PRICE** will be entertained irrespective of deviation clause No.7 of this part of the specification.

14. Revision of tender price by Bidders: -

- [a] After opening of tenders and within the validity of period, no reduction or enhancement in price will be entertained. If there is any change in price, the tender shall stand rejected and the EMD deposited shall be forfeited.
- [b] After opening of price bid if the validity period is not sufficient to place purchase order, the tenderer may be asked by the purchaser to extend the validity period of the bid under the same terms and condition as per the original tender.
 - However, the tender are free to change any or all conditions including price except delivery period of their bids at their own risk, if they are asked by the purchaser to extend the validity period of the bid prior to opening of price bid.

15. Tenderers to be fully conversant with the clauses of the Specification: -

Tenderers are expected to be fully conversant with the meaning of all the clauses of the specification before submitting their tenders. In case of doubt regarding the meaning of any clause, the tenderer may seek clarification in writing from the Senior General Manager (Central Procurement Cell) OPTCL. This, however, does not entitle the Tenderer to ask for time beyond due date, fixed for receipt of tender.

16. Documents to Accompany Bids.

Tenderers are required to submit tenders in the following manner:

Part-I of the Tender shall Contain the following documents.

- [i] Declaration Form. [As per Annexure-I]
- [ii] Earnest Money. [As per **Annexure-VIII**], Tender Cost.
- [iii] Technical specification and Guaranteed Technical Particulars conforming to the Purchaser's Specification along with drawings, literatures and all other required Annexures, duly filled in.
- [iv] Photostat copies of type test certificates of materials/equipment offered as stipulated in the Technical Specification.
- [v] Abstract of Terms & conditions in prescribed proforma as per **Annexure-II.**
- [vi] General Terms & Conditions of supply offer as per Section-II of the Specification.
- [vii] List of orders executed for similar materials/equipment during preceding 2 (two) years indicating the customer's name, Purchase Order No. & Date, date of supply and date of commissioning etc.
- [viii] Data on past experience as per Clause-7 of Section-II of the Specification.
- [ix] GST Compliance Rating. The GST Identification Number(GSTIN) under GST Laws and permanent account number [PAN] of the firm, IT return for last 3 years under Income tax Act are required.
- [x] Audited Balance sheet & profit loss accounts of the bidder, for past (3) three years.
- [xi] Schedule of quantity and delivery in the prescribed Proforma vide Annexure, as appended.
- [xii] List of Orders in hand to be executed.
- [xiii] Deviation schedule.
- [xiv] Local micro & small enterprisers (MSEs) (In the state of Odisha) based in Odisha and registered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC have to submit notarized hard copy of valid registration as local MSE(In the state of Odisha) as above on or before the date & time of submission of techno-commercial bid and upload the scan/soft copy of the same in e-tender portal.
- [xv] The bidder should not have any pending litigation or arbitration with OPTCL with regard to any project or related activity. The bidder should certify/declare the same in unequivocal terms by way of an affidavit duly sworn before a magistrate/notary.
- [xvi] Reverse Auction Process Compliance Form (Annexure-IB)
- [xvii] Certificate of DPIIT

17. Documents/Papers to accompanyPart-II Bid.

- (a) Part II of the tender shall consist of the following
 - (i) Schedule of prices in the prescribed proforma

18. Conditional Offer:

Conditional offer shall not be accepted.

19. General: -

- (i) In the event of discrepancy or arithmetical error in the schedule of price, the decision of the purchaser shall be final and binding on the Tenderer.
- (ii) For evaluation, the price mentioned in words shall be taken if there is any difference in figures and words in the price bid.
- (iii) Notice inviting tender shall form part of this specification.
- (iv) The price bids of the technically and otherwise acceptable bids shall only be evaluated. The EMD of others, if any, shall be returned to the bidders.
- (v) Tenderer can offer any lot or all the lots of the tender, if there are more than one lots. But the tender (bid) must be furnished separately for each lot. For each lot, the tenderer has to submit PART-I & PART-II of the bids separately.
- (vi) It should be distinctly understood that the part-II of the bid shall contain only details/documents relating to price, as outlined in clause-17 mentioned herein above. Inclusion of any of the documents/information etc. shall render the bid liable for rejection.
- (vii) The tenderer must submit the EMD amount, cost of tender document (Form Fee) and Tender processing fee in a sealed cover envelope super-scribing the tender specification number, Tender Notice No & Date of tender clearly on the cover envelope. The said envelope is to be submitted in the office of the purchaser on or before the last date and time of submission of Bids.

20.0 Expenses in respect of OPTCL's representative for witnessing the inspection & testing of the offered equipment/materials at the inspection and testing site.

The testing and inspection of the equipment/ materials at manufacturer works are in the scope of work of the Contractor/Supplier.

OPTCL inspecting officer, on receipt of offer for inspection from the contractor/supplier, proceeds to the manufacturer works to witness the Type/Acceptance/Routine test.

Important:

It is hereby informed to all the bidders that the relevant clauses of the contract specification, pertaining to inspection and testing of equipment/materials, are hereby supplemented with following additional terms and conditions.

The expenses under the following heads, in respect of OPTCL's representative for witnessing the inspection & testing of the offered equipment/materials at the inspection and testing site, shall be borne by the contractor / supplier.

a) Hotel Accommodation:

I. Single room accommodation in 4 star hotel for the OPTCL inspecting officer of the rank of Assistant General Manager (Grade E-6) and above.

- II. Single room accommodation in 3 star hotel for the OPTCL inspecting officer of the rank below Assistant General Manager (Grade E-6).
- N.B.: It is the responsibility of the contractor to arrange the hotel accommodation matching with their inspection and testing schedule, so that the inspecting officer can check-in the hotel one day prior to the date of inspection and check out after the completion of the inspection, subject to availability of the return travel ticket. In case of extended duration of inspection or non-availability of the return travel ticket, Contractor/supplier/manufacturer shall arrange for the extended stay of the inspecting officer in the Hotel accordingly. In case there is no hotel with prescribed standard in and around the place of inspection, contractor/supplier/manufacturer shall suggest alternative suitable arrangement at the time of offer for inspection, which is subjected to acceptability of OPTCL inspecting officer.

b) Journey of the inspecting officer:

- (i) To and fro travel expenditure from the Head Quarters of the inspecting officer to the place of inspection/testing shall be borne by the contractor/supplier/manufacturer. Journey from the Head Quarters of the inspecting officer to the nearest Air Port by train (Ist/IInd A.C) & A/C Taxi then by Air to the place of inspection/testing or to the nearest place of inspection/testing and then by train (Ist/IInd A.C) & A/C taxi to the place of inspection/testing shall be arranged by the contractor/supplier/manufacturer.
- (ii) For train journey, inspecting officer of the rank Assistant General Manager and above shall be provided with 1st class AC ticket and inspecting officer below the rank of Assistant General Manager shall be provided with 2nd class AC ticket.
- (iii) The Air-ticket / train-ticket booking/cancellation is the responsibility of the contractor / supplier.
- (iv) Moreover, if during the journey there is an unavoidable necessity for intermediate travel by road/ waterway/sea-route, the contractor/supplier shall provide suitable conveyance to the inspecting officer for travel this stretch of journey or bear the cost towards this. Any such possibilities shall be duly intimated to OPTCL at the time of their offer for inspection.

c) Local Conveyance:

At the place of the inspection/testing, for local journey of the inspecting officer between Hotel and inspection/testing site and or any other places, Air-conditioned four wheeler vehicle in good condition shall be provided by the contractor/supplier/manufacturer.

d) Following points are also to be considered:

- (i) All the above expenses shall be deemed to be included in the bidder's quoted price for that supply item. Bidder shall not be eligible to raise any extra claim in this regard.
- (ii) Contractor/supplier/manufacturer may assume that only in 40% of the inspection and testing offer cases, OPTCL inspecting officer, not below the rank of Assistant General Manager will witness the inspection and testing.

- (iii) In case of inspection and testing of some critical equipment/materials like Power transformers, OPTCL may depute more than one inspecting officer.
- (iv)Contractor/supplier/manufacturer shall judiciously plan the inspection/testing schedule and place of inspection/testing, so that optimum number of inspection/testing and minimum time shall be required to cover all the equipment/materials of the relevant contract package.
- (v) It shall be the responsibility of the Contractor/Supplier to organize the above tour related matters of OPTCL inspecting officer including the matters related to overseas inspection/testing, if any.

21. Litigation/Arbitration

- (i)- Bidder has to furnish detailed information on any litigation or arbitration arising out of contracts completed or under execution by it over the last five years. A consistent history of litigation by or against the bidder may result in rejection of bid.
- (ii) The bidder should not have any pending litigation or arbitration with OPTCL with regard to any project or related activity. The bidder should certify/declare the same in unequivocal terms by way of an affidavit duly sworn before a magistrate or a notary. Bid furnished by the bidder shall not be eligible for consideration if it is not accompanied by the affidavit. Further, the bid/LOA/LOI shall liable for outright rejection/cancellation at any stage if any information contrary to the affidavit/declaration is detected.

SECTION - II.

GENERAL TERMS AND CONDITIONS OF CONTRACT [G.T.C.C.]

Clause.	<u>Title.</u>	Page.
1.	Scope of the contract.	19
2.	Definition of terms.	19
3.	Manner of execution.	20
4.	Inspection and testing.	20
5.	Training facilities.	21
6.	Rejection of materials.	$\frac{1}{21}$
7.	Experience of bidders.	21
8.	Language and measures.	22
9.	Deviation from Specification.	22
10.	Right to reject/accept any tender.	22
11.	Supplier to inform himself fully.	22
12.	Patent rights etc.	22
13.	Delivery.	23
14.	Despatch Instructions.	23
15.	Supplier's Default Liability.	23
16.	Force Majeure.	23
17.	Extension of Time.	24
18.	Guarantee Period.	24
19.	Bank Guarantee towards Security Deposit,	24
	Payment and Performance.	
20.	Import License.	25
21.	Terms of Payment.	25
22.	Price Reduction Schedule for Delay in	
	Completion of Contract.	25
23.	Insurance.	26
24.	Payment Due from the Supplier.	26
25.	GST rating, Audited Accounts	26
26.	Certificate of exemption from Goods & Services Tax.	26
27.	Supplier's Responsibility.	27
28.	Validity.	27
29.	Evaluation.	27
30.	Minimum qualification criteria of Bidders.	28
31.	Jurisdiction of High Court of ODISHA.	28
32.	Correspondences.	28
33.	Official Address of the Parties to the Contract.	28
34.	Outright rejection of Tenders.	28
35.	Documents to be treated as confidential.	30
36.	Scheme/Projects.	30

PART-I

SECTION-II

GENERAL TERMS AND CONDITIONS OF CONTRACT [G.T.C.C.]

1. Scope of the contract:

The scope of the contract shall be to design, manufacture, supply of equipment as per the specification at the consignee's site, and rendering services in accordance with the enclosed technical specification and bill of quantity.

2.0 Definition of terms:

For the purpose of this specification and General Terms and Conditions of contract [GTCC], the following words shall have the meanings hereby indicated, except where otherwise described or defined.

- 2.1 "The Purchaser" shall mean the Senior General Manager[Central Procurement Cell] for and on behalf of ODISHA POWER TRANSMISSION CORPORATION LTD., Bhubaneswar.
- 2.2 "The Engineer" shall mean the Engineer appointed by the Purchaser for the purpose of this contract.
- 2.3 "Purchaser's Representative" shall mean any person or persons or consulting firm appointed and remunerated by the Purchaser to supervise, inspect, test and examine workmanship and materials of the equipment to be supplied.
- 2.4 "The supplier" shall mean the bidder whose bid has been accepted by the purchaser and shall include the bidder's executives, administrators, successors and permitted assignees.
- 2.5 "Equipment" shall mean and include all machinery, apparatus, materials, and articles to be provided under the contract by the suppliers.
- 2.6 "Contract Price" shall mean the sum named in or calculated the bid.
- 2.7 "General Condition" shall mean these General Terms and Conditions of Contract.
- 2.8 The Specification" shall mean both the technical as well as commercial parts of the specification annexed to or issued with GTCC and shall include the schedules and drawings, attached thereto as well as all samples and pattern, if any.
- 2.9 "Month" shall mean "Calendar month".
- 2.10 Writing" shall include any manuscript, type written, printed or other statement reproduction in any visible form and whether under seal or under hand.
- 2.11 "Basic Price (Taxable Value for goods) at the point of destination" shall mean the price quoted by the bidder for equipment and material at the consignee's store/site. The cost is inclusive of packing, forwarding, freight, insurance and all expenses and taxes and duties at the end of the supplier excluding goods and service tax. The Goods & Service Tax shall be shown in a separate column item wise alongside the Basic Price quoted at the applicable rate in the Tax Invoice. The applicable rate of

GST shall refer to the HSN code of the material supplied. The Basic Price and GST thereon shall be the "FOR Destination Price" as quoted by the bidder.

- 2.12 The term "Contract document" shall mean and include GTCC, specifications, schedules, drawings, form of tender, Notice Inviting Tender, covering letter, schedule of prices or the final General Conditions, any special conditions, applicable to the particular contract.
- 2.13 Terms and conditions not herein defined shall have the same meaning as are assigned to them in the Indian Contract Act, failing that in the Odisha General Clauses Act.

3. Manner of execution:

All equipment supplied under the contract shall be manufactured in the manner, set out in the specification or where not set out, to the reasonable satisfaction of the Purchaser's representative.

4. Inspection and Testing:

- [i] The purchaser's representative shall be entitled at all reasonable times during manufacture to inspect, examine and test at the supplier's premises, the materials and workmanship of all equipment/materials to be supplied under this contract and if part of the said equipment/material is being manufactured in other premises, the supplier shall obtain for the purchaser's representative permission to inspect, examine and test as if the equipment/material were being manufactured in the contractor's premises. Such inspection, examination and testing shall not relieve the supplier from his obligations under the contract.
- [ii] The Supplier shall give to the purchaser adequate time/notice (at least clear 15 days for inside the state suppliers and 20 days for outside the state suppliers) in writing for inspection of materials indicating the place at which the equipment/material is ready for testing and inspection and shall also furnish the shop Routine Test Certificate, Calibration certificates of Testing instruments, calibrated in Govt. approved laboratory with authenticity letter of that laboratory along with the offer for inspection. A packing list along with the offer, indicating the quantity which can be delivered in full truck load/Mini truck load to facilitate issue of dispatch instruction shall also be furnished.
- [iii] Where the contract provides for test at the Premises of the supplier or any of his sub-vendors, the supplier shall provide such assistance, labour, materials, electricity, fuel and instruments, as may be required or as may be reasonably demanded by the Purchaser's representative to carryout such tests efficiently. The supplier is required to produce shop routine test Certificate, calibration certificates of Testing Instruments before offering their materials/equipment for inspection & testing. The test house/laboratory where tests are to be carried out must be approved by the Govt. A letter pertaining to Govt. approved laboratory must be furnished to the purchaser along with the offer for inspection.
- [iv] After completion of the tests, the Purchaser's representative shall forward the test results to the Purchaser. If the test results conform to the specific standard and specification, the Purchaser shall approve the test results and communicate the same to the supplier in writing. The supplier shall provide at least five copies of the test certificates to the Purchaser.

- [v] The Purchaser has the right to have the tests carried out at his own cost by an independent agency whenever there is dispute regarding the quality of supply.
- [vi] If the firm fails to present the offered items for inspection/testing as per their inspection call due to any reason(s) during the visit of inspecting officer at the testing site, the firm shall have to bear all expenses towards repetition of inspection and testing of the total offered quantity or part thereof.

5. Training facilities.

The supplier shall provide all possible facilities for training of Purchaser's Technical personnel, when deputed by the Purchaser for acquiring first-hand knowledge in assembly of the equipment, its erection, commissioning and for its proper operation & maintenance in service, wherein it is thought necessary by the purchaser.

6. Rejection of Materials.

In the event any of the equipment /material supplied by the manufacturer is found defective due to faulty design, bad workmanship, bad materials used or otherwise not in conformity with the requirements of the Specification, the Purchaser shall either reject the equipment/material or ask the supplier in writing to rectify or replace the defective equipment/material free of cost to the purchaser. The Supplier on receipt of such notification shall either rectify or replace the defective equipment/material free of cost to the purchaser within 15 days from the date of issue of such notification by the purchaser. If the supplier fails to do so, the Purchaser may:-

- [a] At its option replace or rectify such defective equipment /materials and recover the extra costs so involved from the supplier plus fifteen percent and/or.
- [b] Terminate the contract for balance work/supplies, with enforcement of penalty Clause as per contract for the un-delivered goods and with forfeiture of Performance Guarantee/ Composite Bank guarantee.
- [c] Acquire the defective equipment/materials at reduced price, considered equitable under the circumstances.

7. Experience of Bidders:

The bidders should furnish information regarding experience particularly on the following points:

- [i] Name of the manufacturer:
- [ii] Standing of the firm and experience in manufacture of equipment/material quoted:
- [iii] Description of equipment/material similar to that quoted, supplied and installed during the last two years with the name(s) of the Organisations to whom supplies were made wherein, at least one (1) certificate shall be from a state/central P.S.U.
- [iv] Details as to where installed etc.
- [v] Testing facilities at manufacturer's works.
- [vi] If the manufacturer is having collaboration with another firm [s], details regarding the same.
- [vii] A list of purchase orders of identical material/equipment offered as per technical specification executed during the last two years along with users certificate. User's

certificate shall be legible and must indicate, user's name, address, designation, place of use, and satisfactory performance of the equipment/materials for at least two years from the date of commissioning. Wherein at least one (1) certificate shall be from a State/Central or P.S.U. Bids will not be considered if the past manufacturing experience is found to be un-satisfactory or is of less than 2 (two) years on the date of opening of the bid and bids not accompanying user's certificate will be rejected.

8. Language and measures:

All documents pertaining to the contract including specifications, schedule, notices, correspondence, operating and maintenance instructions, drawings or any other writing shall be written in English language. The metric system of measurement shall be used exclusively in this contract.

9. **Deviation from specification**:

It is in the interest of the tenderers to study the specification, specified in the tender schedule thoroughly before tendering so that, if any deviations are made by the Tenderers, (both commercial and Technical), the same are prominently brought out on a separate sheet under heading "Deviations Commercial" and "Deviations Technical".

A list of deviations shall be enclosed with the tender. Unless deviations in scope, technical and commercial stipulations are specifically mentioned in the list of deviations, it shall be presumed that the tenderer has accepted all the conditions, stipulated in the tender specification, not- withstanding any exemptions mentioned therein.

10. Right to reject/accept any tender:

The purchaser reserves the right either to reject or to accept any or all tenders if the situation so warrants in the interest of the purchaser. Orders may also be split up between different Tenderers on individual merits of the Tenderer. The purchaser has exclusive right to alter the quantities of materials/ equipment at the time of placing final purchase order. After placing of the order, the purchaser may defer the delivery of the materials. It may be clearly understood by the Tenderer that the purchaser need not assign any reason for any of the above action [s].

11. Supplier to inform himself fully:

The supplier shall examine the instructions to tenderers, general conditions of contract, specification and the schedules of quantity and delivery to satisfy himself as to all terms and conditions and circumstances affecting the contract price. He shall quote price [s] according to his own views on these matters and understand that no additional allowances except as otherwise provided there in will be admissible. The purchaser shall not be responsible for any misunderstanding or incorrect information, obtained by the supplier other than the information given to the supplier in writing by the purchaser.

12. Patent rights Etc.

The supplier shall indemnify the Purchaser against all claims, actions, suits and proceedings for the infringement of any patent design or copy right protected either in the country of origin or in India by the use of any equipment supplied by the

manufacturer. Such indemnity shall also cover any use of the equipment, other than for the purpose indicated by or reasonably to be inferred from the specification.

13. Delivery:-

- [a] Time being the essence of the contract; the equipment shall be supplied within the delivery period, specified in the contract. The Purchaser, however, reserves the right to reschedule the delivery and change the destination if required. The delivery period shall be reckoned from the date of placing the Letter of Intent/Purchase order, as may be specified in LOI/Purchase order.
- [b] The desired delivery period shall be as indicated at Appendix-II (Quantity & Delivery Schedule) of Section-IV (Technical Specification).

14. <u>Dispatch instructions</u>.

I] The equipment / materials should be securely packed and dispatched directly to the specified site at the supplier's risk by Road Transport only.

II] Loading & unloading of Ordered Materials.

It will be the sole responsibility of the supplier for loading and unloading of materials both at the factory site and at the destination site/store.

The Purchaser shall have no responsibility on this account.

15. Supplier's Default Liability.

- [i] The Purchaser may, upon written notice of default to the supplier, terminate the contract in circumstances detailed hereunder.
- [a] If in the judgment of the Purchaser, the supplier fails to make delivery of equipment/material within the time specified in the contract or within the period for which if extension has been granted by the Purchaser in writing in response to written request of the supplier.
- [b] If in the judgment of the Purchaser, the supplier fails to comply with any of the provisions of this contract.
- [ii] In the event, Purchaser terminates the contract in whole or in part as provided in Clause-15 (I) of this section, the Purchaser reserves the right to purchase upon such terms and in such a manner as he may deem appropriate in relation to the equipment/material similar to that terminated and the supplier will be liable to the Purchaser for any additional costs for such similar equipment/material and/or for penalty for delay as defined in clause-22 of this section until such reasonable time as may be required for the final supply of equipment.
- [iii] In the event the Purchaser does not terminate the contract as provided in clause 15(I) of this Section, supplier shall be liable to the Purchaser for penalty for delay as set out in Clause-22 of this section until the equipment is accepted. This shall be based only on written request of the supplier and written willingness of the Purchaser.

16 Force Majeure:

The supplier shall not be liable for any penalty for delay or for failure to perform the contract for reasons of force majeure such as acts of god, acts of the public enemy, acts of Govt., Fires, floods, epidemics, Quarantine restrictions, strikes, Freight

Embargo and provided that the supplier shall within Ten (10)days from the beginning of delay on such account notify the purchaser in writing of the cause of delay. The purchaser shall verify the facts and grant such extension, if facts justify

17. Extension of time:-

If the delivery of equipment/material is delayed due to reasons beyond the control of the supplier, the supplier shall without delay give notice to the purchaser in writing of his claim for an extension of time. The purchaser on receipt of such notice may or may not agree to extend the contract delivery date as may be reasonable but without prejudice to other terms and conditions of the contract.

18. Guarantee period: - (As per clause 35 of the technical specification.

- **[i]** The materials covered by this specification should be guaranteed for satisfactory operation and against defects in design, materials and workmanship for a period of at least **36** [**Thirty six**] **months** from the last date of delivery (In case of delivery in multiple stages, the last date of delivery of each stage delivery shall be considered for this purpose). The above guarantee certificate shall be furnished in triplicate to the purchaser for his approval. Any defect noticed during this period should be rectified/replaced by the supplier free of cost to the purchaser provided such defects are due to faulty design, bad workmanship or bad materials used, within one month upon written notice from the purchaser failing which provision of clause 22 (ii) shall apply.
- [ii] The supplier's liability shall be to the extent of repair/ replacement of such defective equipment/material either faulty defective arising from design or equipment/materials bad workmanship. Such defective and or equipment/materials shall be handed over to the supplier for repair or replacement by a new one, unless otherwise repairable at site. The supplier shall complete the repair/replacement work within the reasonable time frame (as mentioned in clause 22(ii) intimated by OPTCL.

If it becomes necessary for the supplier to replace or repair any defective portions of the equipment/materials the provision of this clause shall apply to portion of the equipment/materials so replaced or repaired until the expiry of the guarantee period.

19. B.G. towards security deposit, 100% payment and performance guarantee:

[i] For manufacturers situated Inside & out side the state of Odisha.

A Composite Bank Guarantee as per the Proforma enclosed at Annexure-VII of the specification for 10% [ten percent] of the taxable value plus GST there on of the purchase order(In case of successful bidder who is a local Micro and small Enterprise(MSEs) (In the state of Odisha), based in Odisha & registered with

respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC 5% (five percent), shall be furnished from any nationalized/scheduled bank having a place of business at Bhubaneswar, to the office of Sr.General Manager [Central Procurement Cell] OPTCL within 30 days from the date of issue of the purchase order.

The BG shall be executed on non-judicial stamp paper worth of Rs.29.00 [Rupees twenty nine] only or as per the prevalent rules, valid for a period of 2 months more than from guarantee period (as indicated this clause-18 of above) from the last date of stipulated delivery period, for scrutiny and acceptance, failing which the supply order will be liable for cancellation without any further written notices. The BG should be accompanied by a confirmation letter from the concerned bank and should have provision for encashment at Bhubaneswar, before the Bank Guarantee is accepted and all concerned intimated. The B.G should be revalidated as and when intimated to you to cover the entire guarantee period.

- [ii] No interest is payable on any kind of Bank Guarantee.
- [iii] In case of non-fulfillment of contractual obligation, as required in the detailed purchase order/Specification, the composite Bank guarantee shall be forfeited.

20. Import License

In case imported materials are offered, no assistance will be given for release of Foreign Exchange. The firm should arrange to import materials from their own quota. Equipment of indigenous origin will be preferred.

21. (A) Terms of Payment.

- i) 100% taxable value of each consignment with 100% Goods and Services Tax in full as applicable will be paid on receipt of materials in good condition at stores/desired site and verification thereof, subject to furnishing and approval of Contract cum Performance Bank Guarantee at the rate of 10% (Ten percent) of Taxable Value plus GST thereon [In case successful bidder is a local Micro and small Enterprise (MSEs),based in Odisha®istered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC, 5% (five percent) in place of 10% (ten percent) will be applicable].
- b. Guarantee certificate,
- c. Test certificate by the Purchaser.
- ii) TDS under GST Laws and Income Tax Act shall be deducted, as applicable and requisite TDS certificate will be issued.
- iii) Any statutory variation due to imposition of new tax or revision in rate of existing tax shall be paid/reimbursed based on scheduled delivery or actual delivery whichever is earlier (i.e. If delivery is within schedule period, statutory variation as applicable shall be paid, and if delivery is made beyond schedule date, any additional financial implication due to statutory variation shall be to the bidder's account)

B] The supplier shall furnish Contract cum Performance Bank Guarantee of appropriate amount (10% or 5%)to OPTCL as indicated in (i) above, within 30 days from the date of issue of the purchase order.

22. Price Reduction Schedule for Delay in Completion of Supply under Purchase Order/Contract

- (i) If the Supplier fails to deliver the materials/equipment within the delivery schedule, specified in the Purchase Order/Contract including delivery time extension, if any, granted with waiver of Price Reduction Schedule, the Purchaser shall recover from the Supplier, Price Reduction Schedule for a sum of half per cent (0.5 per cent) of the Taxable Value of the un-delivered equipment /materials for each calendar week of delay or part thereof. For this purpose, the date of receipted challan shall be reckoned as the date of delivery. The total amount of Price Reduction Schedule shall not exceed five per cent (5%) of the Taxable Value of the un-delivered equipment/materials. Equipment will be deemed to have been delivered only when all its components, accessories and spares as per technical Specification are also delivered. If certain components, accessories and spares are not delivered time. the equipment/materials will be considered delayed until such time as the missing components, accessories and spares are delivered.
- (ii) During the guarantee period, if the Supplier fails to rectify/replace the equipment/material within 30 days from the date of intimation of defect by the purchaser, then the Price Reduction Schedule at the rate of half percent (0.5%) of the Total Taxable Value for each calendar week of delay or part thereof shall be recovered by the purchaser. For this purpose, Price Reduction Schedule shall be reckoned from the 30th day from the date of issue of letter on defectiveness of equipment/material. The total amount of Price Reduction Schedule in this case shall not exceed 10% (TEN PERCENT) of the Purchase Order/Contract amount except GST (i.e. Total Taxable Value). If the defects, so intimated are not rectified or equipment/materials not replaced by the supplier within the guarantee period, then whole of the C.P.B.G. will be forfeited by the purchaser, without any intimation to the supplier.

23. Insurance

The Supplier shall undertake insurance of stores covered by this Specification unless otherwise stated. The responsibility of delivery of the stores at destination in good condition rests with the Supplier. Any claim with the Insurance Company or transport agency arising due to loss or damage in transit has to be settled by the supplier. The Supplier shall undertake free replacement of materials damaged or lost, which will be reported by the consignee within 30 days of receipt of the materials at destination without awaiting for the settlement of their claims with the carriers and underwriters.

24. Payment Due from the Supplier. All costs and damages, for which the supplier is liable to the purchaser, will be deducted by the purchaser from any money, due to the supplier, under any of the contract (s), executed with OPTCL.

25. Rating under Goods and Services Tax and Balance sheet and profit & Loss Account:

- i. Rating under Goods and Services Tax shall be enclosed with the tender.
- ii. Audited Balance Sheet and Profit & Loss Account of the bidder for the previous three years shall be enclosed to assess the financial soundness of the bidder(s).

26. Certificate of Exemption from Goods and Services Tax.

Offers with exemption from Goods and Services Tax shall be accompanied with authenticated proof of such exemption. Authenticated proof for this clause shall mean attested Photostat copy of exemption certificate. Any claim towards Goods and Services Tax shall be paid on actual basis subject to production of authenticated documentary evidence.

27. Supplier's Responsibility.

Notwithstanding anything mentioned in the Specification or subsequent approval or acceptance by the Purchaser, the ultimate responsibility for design, manufacture, materials used and satisfactory performance shall rest with the Tenderers. The Supplier(s) shall be responsible for any discrepancy noticed in the documents, submitted by them along with the bid(s)

28. Validity.

Prices and conditions contained in the offer should be kept valid for a minimum period of **180** days from the date of opening of the tender, failing which the tender shall be rejected.

29. EVALUATION.

- (i) Evaluation of price bids will be on the basis of the FOR DESTINATION PRICE including Goods and Services Tax & other levies as may be applicable. The FORD PRICE shall consist of the following components:
- a) Taxable value of equipment/materials including mandatory spares, if any for maintenance of equipment. (At the discretion of the purchaser)
- b) Goods and Services Tax
- c) Other levies, if any.
- d) Test charges, if any.
- e) Supervision of erection, testing and commissioning charges, if any.
- f) Any other items, as deemed proper for evaluation by the purchaser.
- g) Loading will be made for items not quoted by the bidder at the highest rate quoted by other bidders unless particular item is included in other items.
- h) Any imposition of new tax or revision of tax shall be considered between due date of submission of bids and the date of price bid opening.
- * The Final Ranking of the eligible Bidders for hardware fittings & clamps for conductor shall be on the basis of Total cost of hardware fittings for conductor & earth wire + Total cost of clamps for conductor.

(II) <u>Weightage shall be given to the Following factors in the Evaluation & Comparison of Bids:</u>

In comparing bids and in making awards, the Purchaser will consider other factors such as compliance with Specification, minimum qualification criteria as per clause-30, outright rejection of tenders clause-34 of this tender, relative quality, adaptability of Supplies or services, experience, financial soundness, record of integrity in dealings, performance of materials/equipments earlier supplied, ability to furnish repairs and maintenance services, the time of delivery, capability to perform including available facilities such as adequate shops, plants, equipment and technical Organization.

(III) The local MSE (In the state of Odisha) bidders shall be required to furnish their willingness to match their bid price with that of the lowest evaluated bidder without any price preference and in case they agree, they shall be eligible to get up to 30% of the tendered quantity to be distributed suitably among the willing MSE bidders failing which the said 30% of the tendered quantity be awarded to the lowest evaluated bidder.

(iv) Reverse Auction is hereby incorporated in the referred tender as follows.

STI	RATEGY FOR E-REVERSE AUCTION
1	Bidders are required to go through the guide lines given below and submit their acceptance to the same.
2	e-Reverse Auction (RA) will be conducted in e-tender portal of OPTCL on specified date and time, while bidders shall quote from their own offices/places of their choice. Internet connectivity shall be ensured by the respective agencies/bidders themselves.
3	Demonstration/ training (if not trained earlier) of bidder's nominated person(s), shall be done to explain all the rules related to e-Reverse Auction/ Business Rule document to be adopted.
4	The strategy to be used for reverse auction shall be "DYNAMIC TEMPLATE BIDDING"
Pro	cedure for electronic Reverse Auctioning (e-RA):
5	a. The e-RA shall be conducted on www.tenderwizard/OPTCL.com only. b. Bidder has to submit letter towards agreement to the Process related Terms & Conditions for e-Reverse Auction, as per (Reverse Auction Process Compliance Form at Annexure-IB). In non-receipt of the same, vendors will not be allowed to participate in e-RA.
	c. e-RA shall be carried out after opening of Price bids and completion of Price bid evaluation, which will be intimated only to the techno-commercially qualified bidders by OPTCL as per procedure given below.

- d. OPTCL reserves the right to conduct e-RA and it is obligatory on part of bidder(s) invited to participate in e-RA process once they have responded to the techno-commercial bid.
- Prior intimation/ Notice for RA invitation will be given to techno-commercially qualified bidders regarding the date & time of opening of the e-RA.

The start bid price (SBP) for e-Reverse Auction of each bidder under a particular package shall be the L1 evaluated price for the subject package including Taxes & Duties for the total scope for subject Package. Taking the above discovered L1 price as the upper limit e-RA will be conducted to determine the lowest possible price.

Reverse Auction will be conducted amongst first 50% of the technically qualified bidders arranged in order of prices from lowest to highest, as L1, L2,L3------Ln, and L1 price will be discovered. Minimum of 3 bidders shall be eligible for e RA. (eg. If 4 bidders are financially evaluated then the L1, L2 and L3 bidders shall be eligible for e-RA). Number of bidders eligible for participating in RA would be rounded off to next higher integer value if number of technically qualified bidders is odd (e.g. if 7 bids are technically qualified, then RA will be conducted amongst L1 to L4).

However, in case only two bidders are found to be responsive, e-RA would be carried out with both the parties without any elimination. However, OPTCL reserves the right to invite the evaluated L1 bidder for negotiation without conducting the e-RA.

In case of price submitted by any bidder is found to be abnormal, OPTCL reserves the right to reject the bid of the bidder(s).

Rank of bidders would be displayed as per the total cost to OPTCL, i.e including Taxes and Duties payable by OPTCL as per the provisions of the biding document & after e-RA process is over.

- Names of bidders/ vendors shall not be disclosed during the e-RA process.

 Name of bidders/ vendors shall be anonymously masked in the e-RA process.
 - (i) In case of RA, start/ reference price and step value of decrement shall be indicated to the bidders at the start of the auction. Any participating bidder can bid one or multiple step decrement lower than the prevailing lowest bid at that time. The Bidder shall be able to view Bid Start Price, Bid Decrement

- Value, Prevailing Lowest Bid value, last Bid Placed by him and time left for bidding.
- (ii) The step value of decrement in a package to be offered by bidder (the minimum amount of reduction in the total bid price including all taxes & duties during auction), shall be kept at 0.15% of L1 bidder's final evaluated price (or) at approved amount as decided by OPTCL.
- (iii) Bidders can only quote any value lower than their previous quoted price. However, at no stage, increase in Price will be permissible.
- (iv) At any point during Reverse Auction, bidding Price field shall remain enabled for the bidders. The total reverse auction period shall be unlimited & the initial auction period (1st slot) will be of thirty (30) minutes with provision of auto extension by (10) ten minutes from the schedule/ extended closing time. If any fresh lower bid is received in last ten minutes of auction period or extended auction period, the auction shall get extended automatically for another 10 minutes. In case, there is no bid received during schedule/extended slot, the Auction shall get closed automatically without further extension.
- (v) However, bidders are advised not to wait till the last minute or last few seconds to enter their bid during the period of e-reverse auction to avoid complication related with internet connectivity, network problem, system crash down, power failure etc.
- After conclusion of e-Reverse Auction i.e (Closing Price in Reverse Auction will be taken as offered price by the L1 bidder), decrease in price of individual head of the template shall be considered proportionately on all individual line items of the respective head of the price schedule of the successful L1 bidder.

Any bid received at the tender wizard server end subsequent to closure of the e-RA shall be summarily rejected and shall not be considered as a valid bid under whatsoever circumstances. For this purpose, tender wizard server log shall prevail.

The bidder shall not involve himself or any of his representatives in price manipulation of any kind directly or indirectly by communicating with other bidders.

During Reverse Auction, If no bid is received within the specified time, OPTCL, at its discretion, may decide to close the reverse auction process/ proceed with conventional mode of tendering [Evaluation of Part-II (price bid) submitted by bidders earlier].

9 Consequent upon completion of e-Reverse Auction, OPTCL's decision on award of contract shall be final and binding on the bidders.

OPTCL shall be at liberty to call the L1 bidder for further process/ negotiation and also at liberty to cancel the e-reverse auction process/ re-tender at any time, without assigning any reason thereof. OPTCL can decide to reschedule or cancel any reverse auction: the bidders shall be informed accordingly.

OPTCL/ Service Provider shall not have any liability to bidders for any interruption or delay in access to the e-Tender site/ Reverse Auction link irrespective of the cause.

(Reverse Auction Process Compliance Form)

(Annexure-IB)

(To be incorporated in the bid document).

(To be submitted on letter head of the bidding company with sign and stamp and along with Technical bid)

To,

Sr.GM (CPC), OPTCL

Bhubaneswar-751010, Odisha

Sub: Agreement to the Process related Terms & Conditions for e-Reverse Auction.

Dear Sir,

This letter is to confirm that:

- The undersigned is authorized representative of the company.
- We have studied the Commercial Terms and the Business rules governing the Reverse Auction as mentioned in your tender and confirm our agreement to that.
- We also confirm that we have gone through the auction manual and have understood the functionality of the same thoroughly.
- We, hereby, confirm that we will honour the Bids placed by us during the tendering/ e- Reverse auction process as called as e-RA.
- We also confirm that we will accept our Rank / Position that will be displayed when the Bidding Time for the Online Reverse Auction is over.

With regards,

Signature with Designation with company seal Name & Address

Person having power of attorney for the subject package.

30.Minimum Qualification Criteria of Bidders.

(The following supersedes any other criteria indicated elsewhere in the document)

All the prospective bidders are requested to note that their bids for tendered equipment can only be considered for evaluation if:

- 1. The bidder should have manufacture and supply experience of above rated or higher capacity equipment for a minimum period of **2 (two) years** as on the date of opening of the tender.
- 2. At least 50% of the tendered quantity. Of above rated or higher capacity equipment should have been supplied within the above-stipulated period. .[Note: "within above stipulated period:- within 2(two) years from the date of opening of this tender].
- 3. The above rated or higher capacity equipment should have at least 2 (two) years successful performance from the date of commissioning. At least one of the performance certificates shall be submitted from Govt. of India/State Govt.(s) or their undertakings.
- 4. The Bidder must possess bureau of Indian Standard Certification (ISI mark).
- 5. The bidder must possess valid ISO 9001:2008 certification for Manufacturer/Supplier.
- 6. The Bidder should have adequate infrastructural facility for "After sales service"
- 7. Copies of documents, defining the constitution or legal status, place of registration and principal place of business of the company or firm or partnership or collaborator or parent Company etc. shall be furnished along with the bid.
- 8. The Bidder should have conducted type tests on the tendered equipments/materials in Government approved laboratory within **five years** from the date of opening of the tender.
- 9. Even though the Bidders meet the above qualifying criteria, they are subject to be disqualified if they have
 - a) Made misleading or false representations in the forms, statements and attachments, submitted in proof of qualification requirements and/or
 - b) Record of poor performance such as not properly completing the contract, inordinate delays in completion of supply, litigation history or financial failure etc.
- 10. Notwithstanding anything stated above, the purchaser reserves the right to assess the Bidder's capability & capacity to perform the contract should circumstances warrant such an assessment in the overall interest of the purchaser.

NOTE: The offers of bidders not satisfying any of the above "bid qualification requirements" are likely to be rejected.

Registration certificate of DPIIT:

As per Office Memorandum No.F.No.6/18/2019-PPD, Ministry of Finance, Dept. of Expenditure Public Procurement Division, New Delhi and Office Memorandum No. FIN-CON-MISC-0007/2019/27945/F Dated.16.10.2020 of Finance Department, Govt. of Odisha "Any bidder from a country which **shares a land border with India** will be eligible to bid in any procurement whether goods, services (Including consultancy services and nonconsultancy services) or works (including turnkey projects) only if the bidder is registered with the Competent Authority, DPIIT (i.e. Department for Promotion of Industry and Internal Trade)". Pursuant to decision of Govt. of India prescribing imposition of restriction on public procurement from bidders of certain countries on ground of defence of India or matters directly or indirectly related thereto, the Office Memorandum No. 4939/F, dated: 13.02.2012 of Finance Department, Govt of Odisha has been amended vide Office Memorandum No 27945 Dtd 16.10.2020 by inserting sub-para-3 (vii) to para-3 thereof. Prescribing the restriction on procurement made by the State Govt., State Public Sector Undertaking including local bodies etc. and directing no procurement shall be made in violation of such restrictions, it is hereby clarified that the provisions of the same shall be applicable for the tenders for works/procurement/Service in OPTCL in both ongoing (Techno-Commercial bid not opened) and future tenders.

The tender documents of OPTCL shall contain following additional clauses and certificate formats.

A. To be incorporated as qualifying requirement of bidder /certificates in case of tenders for Works (including Turn-key works)

- I. Any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority as per requirement of Govt. of India.
- II. "Bidder" (including the term 'tenderer', 'consultant' or 'service provider' in certain contexts) means any company, including any member of a consortium or joint venture (that is a company),
- III. "Bidder from a country which shares a land border with India" for the purpose of this Order means:
 - a. An entity incorporated, established or registered as company in such a country; or
 - b. A subsidiary company of an entity incorporated, established or registered in such a country 'or
 - c. An entity substantially controlled through entities incorporated , established or registered in such a country ; or
 - d. An entity whose beneficial owner is situated in such a country; or
 - e. An Indian (or other) agent of such an entity; or
 - f. A consortium or joint venture where any member of the consortium or joint venture falls under any of the above.
- IV. The beneficial owner for the purpose of (iii)(d) above will be as under:
 - **1.** In case of a company the beneficial owner is the natural person(s), who, whether acting along or together, or through one or more juridical person, has a controlling ownership interest or who exercises control through other means.

Explanation-

- a. "Controlling ownership interest" means ownership of or entitlement to more than twenty-five per cent of shares or capital or profits or the company.
- b. "Control" shall include the right to appoint majority of the directors or to control the management or policy decisions including by virtue of their shareholding or management rights or shareholders agreements or voting agreement;
- 2. Where no natural person is identified under (1) above, the beneficial owner is the relevant natural person who hold the position of senior managing official;
- V. An Agent is a person employed to do any act for another, or to represent another in dealings with third person.
- VI. The successful bidder shall not be allowed to sub-contract works to any contractor from a country which shares a land border with India unless such contractor is registered with the Competent Authority.

Certificate (to be furnished in bidder company's letter head)

I have read the clause regarding restrictions on procurement from a bidder of a country which shares a land border with India and on sub-contracting to contractors from such countries; I certify that this bidder is not from such a country or, if from such a country, has been registered with the Competent Authority and will not sub-contract any work to a contractor from such countries unless such contractor is registered with the Competent Authority. I hereby certify that this bidder fulfils all requirements in this regard and is eligible to be considered. [Where applicable evidence of valid registration by the Competent Authority shall be attached.

B. To be incorporated as qualifying requirement of bidder /certificates in case of tenders for procurement of goods/services(including consultancy and non-consultancy)

- I. Any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority as per requirement of Govt. of India
- II. "Bidder" (including the term 'tenderer', 'consultant' or 'service provider' in certain contexts) means any person or firm or company, including any member of a consortium or joint venture (that is an association of several persons, or firms or companies), every artificial juridical person not falling in any of the descriptions of bidders stated herein before, including any agency branch or office controlled by such person, participating in a procurement process.
- III. "Bidder from a country which shares a land border with India" for the purpose of this Order means:
 - a. An entity incorporated, established or registered in such a country; or
 - b. A subsidiary of an entity incorporated, established or registered in such a country 'or
 - c. An entity substantially controlled through entities incorporated , established or registered in such a country ; or
 - d. An entity whose beneficial owner is situated in such a country; or
 - e. An Indian (or other) agent of such an entity; or
 - f. A natural person who is a citizen of such a country; or

- g. A consortium or joint venture where any member of the consortium or joint venture falls under any of the above.
- IV. The beneficial owner for the purpose of (iii)(d) above will be as under:
 - 1. In case of a company or Limited Liability Partnership, the beneficial owner is the natural person(s), who, whether acting along or together, or through one or more juridical person, has a controlling ownership interest or who exercises control through other means.

Explanation-

- a. "Controlling ownership interest" means ownership of or entitlement to more than twenty-five per cent of shares or capital or profits or the company.
- b. "Control" shall include the right to appoint majority of the directors or to control the management or policy decisions including by virtue of their shareholding or management rights or shareholders agreements or voting agreement;
- 2. In case of a partnership firm, the beneficial owner is the natural person(s) who, whether acting along or together, or through one or more juridical person, has ownership or entitlement to more than fifteen per cent of capital or profits of the partnership;
- 3. In case of an unincorporated association or body of individuals, the beneficial owner is the natural person(s), who, whether acting along or together, or through one or more juridical person, his ownership of or entitlement to more than fifteen per cent of the property or capital or profits of such association or body of individuals;
- 4. Where no natural person is identified under (1) or (2) or (3) above, the beneficial owner is the relevant natural person who hold the position of senior managing official;
- 5. In case of a trust, the identification of beneficial owner(s) shall include identification of the author of the trust, the trustee, the beneficiaries with fifteen per cent or more interest in the trust and any other natural person exercising ultimate effective control over the trust through a chain of control or ownership.
- V. An Agent is a person employed to do any act for another, or to represent another in dealings with third person.

Certificate (to be furnished in bidder's letter head)

I have read the clause regarding restrictions on procurement from a bidder of a country which shares a land border with India; I certify that this bidder is not from such a country or, if from such a country, has been registered with the Competent Authority. I hereby certify that this bidder fulfils all requirements in this regard and is eligible to be considered. [Where applicable, evident of valid registration by the Competent Authority shall be attached.}

31. Jurisdiction of the High Court of Odisha.

Suits, if any, arising out of this contract shall be filed by either Party in a court of Law to which the jurisdiction of High court of Odisha extends.

32. Correspondences.

- i) Any notice to the supplier under the terms of the contract shall be served by Registered Post or by hand at the Supplier's Principal Place of Business.
- ii) Any notice to the Purchaser shall be served at the Purchaser's Principal Office in the same manner.

33. Official Address of the Parties to the Contract

The address of the parties to the contract shall be specified:-

- [i] Purchaser: Senior General Manager (Procurement) (CPC) OPTCL
 Bhubaneswar-751022 (Odisha), Telephone No. 0674 2541801
 FAX No. 0674 2542964
- [ii] Supplier: Address

Telephone No.

Fax No.

34. Outright Rejection of Tenders

Tenders shall be out rightly rejected if the followings are not complied with.

- [i] The tenderer shall submit the bid in electronic mode only and shall submit the tender cost on or before the date and time of submission of technical bid.
 - In case of local Micro and small Enterprises(MSEs)(In the state of Odisha), based in Odisha ®istered with respective DICs, Khadi, Village, Cottage & Handicrafts Industries, OSIC and NSIC participating in the tender they have to submit notarised hard copy of valid registration as local MSE as above on or before the date and time of submission of technical bid.
- [ii] The tenderer shall submit the bid in electronic mode only
- [iii] The Tender shall not be submitted telegraphically or by FAX.
- [iv] The prescribed EMD shall be submitted on or before the date and time of submission of technical bid.
- [v] The Tender shall be kept valid for a minimum period of 180 days from the date of opening of tender.
- [vi] The Tender shall be submitted in two parts as specified.
- [vii] The Tenders shall be accompanied by a list of major supplies effected prior to the date of opening of tender. Data of at least 3 (three) years shall be furnished.
- [viii] The tenderer shall upload the scanned copy of latest type test certificates (for the tests, carried out on the tendered equipments, being offered). Such type tests should have been conducted within last five years from the date of opening of this tender in a Government approved laboratory/CPRI in presence of any Government Organization's representative(s).
- [ix] The schedule of prices should be filled up fully to indicate the break-up of the prices including taxes and duties. Incomplete submission of this schedule will make the tender liable for rejection. <u>Vide Clause-4(ii) of Part-II..</u>
- [x] The Tenderer should quote **'FIRM'** price only and the price should be kept valid for a minimum period of **180 days** from the date of opening of the tender.

- [xi] The tenderer shall upload the scanned copy legibly written user's certificate to prove the satisfactory operation of the offered equipments/materials for a minimum period of 2 (two) years from the date of commissioning/use as per the tender specification. User's certificate shall include the detailed address of the user with Equipment/Material, Name and type as per this specification, number of years of satisfactory use/operation & date of issue of this user's certificate with official seal written in English only & clearly visible must be furnished. At least one of the user's certificates shall be from state or Central Govt. or their Undertakings.
- [xii] Guaranteed Technical particulars & Abstract of terms and Conditions should be filled in completely.
- (xiii) (a) Detailed information on any litigation or arbitration arising out of contract completed or under execution by it over the last five years. A consistent history of litigation by or against the bidder may result in rejection of bid.
 - (b) The bidder should not have any pending litigation with OPTCL with regard to any project or related activity. The bidder should certify/declare the same in unequivocal terms by way of an affidavit duly sworn before a magistrate or a Notary. Bid furnished by the bidder shall not be eligible for consideration if it is not accompanied by the affidavit. Further the bid / LOA/ LOI shall be liable for outright rejection/ cancellation at any stage if any information contrary to the affidavit / declaration is detected.

35. Documents to be treated as confidential.

The supplier shall treat the details of the specification and other tender documents as private and confidential and these shall not be reproduced without written authorization from the Purchaser.

36. Scheme/Projects

SECTION - III.

LIST OF ANNEXURES

[I TO XV]

[PAGE 32 TO 47]

The following schedules and proforma are annexed to this specification and contained in Section-III as referred to in the relevant clauses.

1.	Declaration form	ANNEXURE-I	
2.	E-Reverse Auction Compliance Form	ANNEXURE-I(B)	
3.	Abstract of terms and conditions to accompany Section-II of Part-I	ANNEXURE-II	
4.	Schedule of Quantity and Delivery	ANNEXURE-III	
5	Abstract of price component [to accompany Part-II of this specification]	ANNEXURE-IV	
6.	Schedule of prices to accompany Part-II	ANNEXURE-V	
7.	Bank Guarantee form for earnest money deposit	ANNEXURE-VI	
8.	Composite Bank Guarantee form for security deposit, payment and performance	ANNEXURE-VII	
9.	Chart showing particulars of E.M.D.	ANNEXURE – VIII	
10.	Data on Experience.	ANNEXURE – IX	
11.	Schedule of spare parts.	ANNEXURE-X	
12.	Schedule of Installations.	ANNEXURE-XI	
13.	Schedule of deviations(Technical)	ANNEXURE-XII(A)	
14.	Schedule of deviations(Commercial)	ANNEXURE-XII(B)	
15	Litigation/Arbitration	ANNEXURE-XIII	
16	DPIIT Certificate	ANNEXURE-XIV	
17	Affidavit of bidder	ANNEXURE-XV	
		i e	

LIST of Documents

The following documents are to be attached in the below name

- 1.PAN
- 2.GSTIN
- 3.Income tax return
- 4. Audited B/s & Profit loss account
- 5. Certificate of incorporation
- 6. E payment proof of tender cost

ANNEXURE - I

DECLARATION FORM

To

The Sr. General Manager (CPC) OPTCL Head Qrs.BBSR,751022

Sub:- Tender Specification No	
-------------------------------	--

Sir,

- 1. Having examined the above specification together with terms & conditions referred to therein * I/We the undersigned hereby offer to supply the materials/equipment covered therein complete in all respects as per the specification and General conditions, at the rates, entered in the attached contract schedule of prices in the Tender.
- 2. *I/We hereby undertake to have the materials/equipment delivered within the time specified in the Tender.
- 3. * I/We hereby guarantee the technical particulars given in the Tender supported with necessary reports from concerned authorities.
- 4. * I/We certify to have submitted the bid electronically by remitting *cash/money order/D.D./ remitting the cost of tender, herewith and this has been acknowledged by your letter/ money receipt No. Dated,
- 5. In the event of Tender, being decided in *my/our favour, * I/We agree to furnish the Composite B.G. in the manner, acceptable to ODISHA POWER TRANSMISSION CORPORATION LTD., and for the sum as applicable to *me/us as per clause-19 of section-II of this specification within 15 days of issue of letter of intent/purchase order failing which *I/We clearly understand that the said letter of Intent/Purchase order will be liable to be withdrawn by the purchaser, and the EMD deposited by us shall be forfeited by OPTCL.

Signed this day of Yours faithfully

Signature of the Tenderer with seal of the company

[This form should be dully filled up by the tenderer and uploaded at the time of submission of tender.]

* (Strikeout whichever is not applicable).

(Annexure-IB)

(Reverse Auction Process Compliance Form)

(To be submitted on letter head of the bidding company with sign and stamp and along with Technical bid)

To

The Sr. General Manager (CPC),

OPTCL, Bhubaneswar-751010, Odisha

Sub: Agreement to the Process related Terms & Conditions for e-Reverse Auction.

Dear Sir,

This letter is to confirm that:

- The undersigned is authorized representative of the company.
- We have studied the Commercial Terms and the Business rules governing the Reverse Auction as mentioned in your tender and confirm our agreement to that.
- We also confirm that we have gone through the auction manual and have understood the functionality of the same thoroughly.
- We, hereby, confirm that we will honour the Bids placed by us during the tendering/ e-Reverse auction process as called as e-RA.
- We also confirm that we will accept our Rank / Position that will be displayed when the Bidding Time for the Online Reverse Auction is over.

With regards,

Signature with Designation with company seal

Name & Address of Person having power of attorney for the subject package.

NNEXURE-II

ABSTRACT OF GENERAL TERMS AND CONDITIONS OF CONTRACT [COMMERCIAL] TO ACCOMPANY PART-I

(To be filled up by the tenderer as indicated in the excel sheet)

1	Whether the material/equipment offered conforms to the OPTCL'S specification (If not, specify the deviations in Annexure).	Yes/No
2.a.i	Cost of Tender Document:	Submitted /Not submitted
2.a.ii	OPTCL Money Receipt No. & Date / D.D No & Date.	
2.b.i	Earnest money furnished.	Submitted /Not submitted
2.b.ii	Bank Guarantee No. & Date / D.D No. & Date.	
2.c.i	Tender Processing Fee:	Submitted /Not submitted
2.c.ii	D.D No. & Date.	
3	Manufacturer's supply experience including user's certificate uploaded or not. [As per clause No.7 of Section-II.]	Yes/No
4.a.i	Commercial Deviations to the specification if any	Yes/No
4.a.ii	If Yes, [list uploaded or not, As per clause-9 of the Section-II	Yes/No
4.b.i	Technical Deviations to the specification if any	Yes/No
4.b.ii	If Yes, list uploaded or not, As per clause-9 of the Section-II	Yes/No
5	Delivery (Period in months from the date of issue of PO)	
<mark>6</mark>	Guarantee: - Whether agreeable to OPTCL's terms[As per clause-18 of Section-II].	Yes/No
<mark>7</mark>	Whether agreeable to furnish Composite B.G. in case his tender be successful [As per clause-19 of Section-II]	Yes/No
8	Terms of payment:- Whether agreeable to OPTCL's terms or not [As per clause-21 of Section-II]	Yes/No
9	Nature of price:- FIRM	Yes/No
10	Price Reduction: - Whether agreeable to OPTCL's terms or not (As per clause- 22 of Section-II)	Yes/No

11	Whether STCC/ P&L A/C, Balance Sheet for the required period are uploaded as per clause-25 of Section-II	Yes/No
12	Validity: - Whether agreeable to OPTCL's terms or not[As per clause-28 of Section-II]	Yes/No
13	Whether recent type test certificates from any Government approved laboratory is uploaded or not. [As per clause-30[viii] of section-II]	Yes/No
14	Whether guaranteed technical particulars are uploaded or not	Yes/No
15	Whether dimensional design/drawings uploaded or not	Yes/No
16	Whether materials are ISI/ISO marked.	Yes/No
17	Manufacturer's name and its trademark	
18	Whether registered under GST Laws.	Yes/No
19	Whether declaration form, duly filled in, uploaded or not	Yes/No

Place: -	
Date: -	Signature of the Tendere
with se	al of the company

Place:
Signature of the Tenderer

with seal of the company

ANNEXURE-III

SCHEDULE OF QUANTITY AND DELIVERY

(To be filled up by the tenderer)

SL No	Description of materials	Quantity required	Desired Delivery	Destinati on	Rema rks.
1	2	3	4	5	6

Signature of Tenderer

with seal of Company

ANNEXURE-IV

ABSTRACT OF PRICE COMPONENT [TO ACCOMPANY PRICEBID]

(To be filled up by the tenderer as indicated in the excel sheet)

S1.No.	Description	To be filled by the bidder.
1	Price basis	F.O.R. Purchaser's destination Stores/site.(Taxable value including packing forwarding, Freight, Insurance, unloading)
2	HSN Code of the Item	•
3	GST Identification Number (GSTIN) of the firm	
4	Whether Intra-state supply(i.e. from inside Odisha) or Inter-state supply(i.e from outside Odisha). select from dropdown list	
5	Rate of CGST	-
<mark>6</mark>	Rate of OGST.	-
7	Rate of IGST.	
8	Rate of Goods and Services Tax on supervision of erection testing and commissioning	
9	Nature of price.	
10	We hereby undertake and declare that implication of lower Tax and Input Tax Credit benefit as per anti-profiteering (under Section 171 of CGST Act) and other provisions under GST Laws have been fully passed on to the purchaser while quoting the price.	Agreed
11	Any imposition of new tax or revision of tax shall be paid/reimbursed at the time of dispatch, scheduled or actual whichever is lower (i.e. If delivery is within schedule period, tax variation as applicable shall be paid, and if delivery is made beyond schedule date, any additional financial implication due to statutory variation in tax shall be to bidder's account). (Indicated-Yes/No)	

NB:- Abstract of price component shall be done for equipment/material offered, for testing & commissioning charges, if any. All the above prices will be taken during bid price evaluation

Place:	Signature of the Bidder
	The state of the s
Date:	with seal of the company

ANNEXURE-V.

SCHEDULE OF PRICES TENDER SPECIFICATION No.

Ite m No.	Description.	Qty (unit)	Unit Taxable Value at destination store/ site including transformer oil & other accessories & testing as per spec.
1.	<mark>2.</mark>	3.	4.

<u>Unit</u>	Unit landing Cost including	Total landing cost Including all taxes & duties.
GST	all taxes & Duties.	
<mark>5.</mark>	6= (4+5)	7= (6*3)

Erection Cost in INR Rs.			Grand Total amount in Rs.
Unit Erection Cost Unit GST Total Erection Cost		13+16	
14	15	16	17

NB: -

1. The tenderer should fill up the schedule properly and in full in Excel file of etender mode. The tenderer should fill up the schedule properly and in full. The tender will be rejected, if the schedule of price is submitted in incomplete form. No post tender correspondence will be entertained on break-up of prices. Also, the supplier should agree for delivery at sub-station site.

- 2. The Tenderer shall give an undertaking in part-I of the bid that, any implication of lower Tax and Input Tax Credit benefit have been fully passed on to the purchaser as per anti-profiteering and other provisions under GST Laws while quoting the tender price.
- 3. Conditional offers will not be acceptable.
- 4. The bidder is to clearly indicate the period up to which the tax holidays are available to them.
- 5. Price bid in any other format will not be acceptable and the offer will be rejected.
- 6. All the above charges will be taken into account, during bid price evaluation.

ANNEXURE-VI

[PROFORMA FOR BANK GUARANTEE FORM FOR EARNEST MONEY DEPOSIT]

(To be Stamped in accordance with Stamp Act and the Non-Judicial Stamp Paper of appropriate value should be in the name of Issuing Bank)

• •
Ref No:
Bank Guarantee No
Date:
BG Amount:
Validity Period:
This Guarantee Bond is executed this day of by us the Bank at, P.O, Dist, State and Code No
Whereas the ODISHA POWER TRANSMISSION CORPORATION Limited, Janpath, Bhubaneswar, a company constituted under the Companies Act-1956 (hereinafter called OPTCL) has invited Tender vide e-NIT No
1. Now, therefore, in accordance with Notice Inviting Tender (e-NIT) No

w to	ANSMISSION CORPORATION Ltd., Bhubaneswar an amount not exceeding Rs to OPTCL., chout any reservation. The guarantee would remain valid up to [Date] and if any further extension this is required, the same will be extended on receiving instruction from on whose half this Bank Guarantee has been issued.
2.	Ve, the [indicate the name of the Bank, Address, Code] do hereby further undertake to pay the amounts due and payable under this guarantee without any demur, merely on a demand from OPTCL. Any such demand made on the Bank shall be conclusive as regards the amount due and payable by the Bank under this guarantee. However, our liability under this guarantee shall be restricted to an amount not exceeding Rs (Rupees in words)
3. \	We undertake to pay to OPTCL any money so demanded not withstanding any dispute or disputes so raised by the bidder in any suit or proceeding instituted/pending before any court or tribunal relating thereto, our liability under this present being absolute and unequivocal. The payment so made by us under this bond shall be a valid discharge of our liability for payment thereunder and the bidder shall have no claim against us for making such payment.
4.	Ve, the
5.	We the Bank further agree with OPTCL that OPTCL shall have the fullest liberty without our consent and without affecting in any manner our obligations hereunder to vary any of the terms and conditions of the said Bid or to extend time of performance by the said Bidder from time to time or to postpone for any time or from time to time any of the powers exercisable by OPTCL against the said Bidder and to forbear or enforce any of the terms and conditions relating to the said Bid and we shall not be relieved from our liability by reason of any such variation, postponement or extension granted to the Bidder or for any forbearance, act or omission on the part of OPTCL or any indulgence by OPTCL to the said Bidder or by any such matter or thing whatsoever which under the law relating to sureties would, but for this provision, have the effect of so relieving us.
	nis guarantee will not be discharged due to the change in the name, style and constitution of the Bank or of the Bidder.

	We [indicate the name of Bank, Address &Code] lastly undertake not to revoke this guarantee during its currency except with the previous consent of OPTCL in writing
8.	We, theBank (Name, Address & Code) further agree that this guarantee shall also be invokable at our place of business at Branch of Bhubaneswar (indicate Name, Address & Code of the Branch at Bhubaneswar) in the State of Odisha."
"「	Notwithstanding anything contained herein"
a) (on	Our liability under the bank guarantee shall not exceed Rs(Rupees in words)ly.
b) ⁻	This Bank guarantee shall be valid up to
am	We or our Branch at Bhubaneswar < Mention Name, Address & Code> shall be liable to pay guaranteed nount or any part thereof under this guarantee only if you serve upon us at Branch of Bhubaneswar a itten claim or demand on or before
the	The Bank Guarantee is issued in paper form and Advice transmitted through SFMS with required details to e beneficiary's advising bank (ICICI Bank Bhubaneswar, IFSC Code ICIC0000061).
	Dated, theDay of
Foi	r [Indicate name of Bank]
Sig	nature
Ful	II name
De	signation
Po	wer of Attorney No
Da	te
Sea	al of the Bank

WITNES	SS: (SIGNATURE WITH NAME AND ADDRESS)
(1)	
Signatu	ıre
Full nar	me
(2)	
Signatu	ıre
Full nar	me
N.D.	
N.B.:	
1. Na	me of the Bidder.:
2. BG	i No & Date :
3. Am	nount (In Rs.):
4. Va	lidity up to :
5. E-N	NIT No
6. Pa	ckage/Works No
7. Na	me, Address & Code of Issuing Bank:
8. Na	me, Address & Code Bhubaneswar Branch of the Issuing Bank:
9.	The Bank Guarantee shall be accepted after getting SFMS advice as per details below.

Format for SFMS details

(The Unique Identifier for field 7037 is "OPTCL541405793")

Sl. No	PARTICULARS	ТҮРЕ	DETAILS
1	Type of Bank Guarantee	Mandatory	EMD
2	Currency & Amount	Mandatory	
3	Validity Period(from—to)	Mandatory	

4	Effective Date	Mandatory	
5	End date of lodgment of Claim	Mandatory	
6	Place of lodgment of claim	Mandatory	Bhubaneswar,
			Branch Name of
			Bhubaneswar
			Branch code of
			Bhubaneswar
			Branch Address at
			Bhubaneswar
7	Issuing Branch IFSC Code	Mandatory	
8	Issuing Branch name & address	Mandatory	
9	Name of applicant and its details	Mandatory	
10	Name of Beneficiary and its details	Mandatory	
11	Beneficiary's Bank/Branch and	Mandatory	ICICI Bank Ltd
	IFSC Code		IFSC Code-ICIC0000061
12	Beneficiary's Bank/Branch name	Mandatory	ICICI Bank Ltd
	and address		Bhubaneswar Main Branch,
			Bhubaneswar
13	Sender to receiver information	Mandatory	
14	Purpose of Guarantee	Mandatory	EMD
15	Reference/Description of the underlined tender/contract	Mandatory	NIT No

ANNEXURE-VII

[PROFORMA FOR COMPOSITE BANK GUARANTEE FOR SECURITY DEPOSIT PAYMENT AND PERFORMANCE]

be in the name of the Issuing Bank.)
Ref No:
Bank Guarantee No Date:
BG Amount:
Validity Period:
This Guarantee Bond is executed this day of by us the Bank at, P.O, Dist, State and Code No
Whereas the ODISHA POWER TRANSMISSION CORPORATION Limited, Janpath, Bhubaneswar, a company constituted under the Companies Act-1956 (hereinafter called OPTCL) has issued Letter of Award (LOA) No
1. Now therefore, in accordance with the terms and conditions of LOA No dated for the due fulfillment by the said Contractor of the terms and conditions contained in the said agreement, on production of a Bank Guarantee for Rs (Rupees) only, we the bank [Indicate bank Name , Address & Code] (hereinafter referred to as "the Bank") at the request of M/s/Shri contractor do hereby undertake to pay to OPTCL, an amount not exceeding Rs (Rupees) only .
2. We, the Bank [indicate the name of the Bank, Address & Code] do hereby undertake to pay the amounts due and payable under this guarantee without any demur, merely on a demand from OPTCL. Any such demand made on the bank shall be conclusive as regards the amount due and payable by the bank under this guarantee. However, our liability under this guarantee shall be restricted to an amount not exceeding Rs (Rupees
3. We, the

(To be stamped in accordance with Stamp Act and the Non-Judicial stamp paper of appropriate value should

remain in full force and effect dur enforceable till all the dues of OPT claims satisfied or discharged or till	Bank further agree that the guarantee herein contained shalling the aforesaid period of days and it shall continue to be so CL under or by virtue of the said Agreement have been fully paid and its OPTCL certifies that the terms and conditions of the said Agreement have by the said contractor and accordingly discharges this guarantee.
Name, Address & Code of the Brand	s guarantee is made on us or our Branch Office at Bhubaneswar <mentior ch Office at Bhubaneswar of issuing Bank> in writing on or before n all liability under this guarantee thereafter.</mentior
agree with the Board that OPTCL s any manner our obligations hereur time or performance by the said co time any of the powers exercisable the terms and conditions relating t any such variation postponement o act or omission on the part of OPT	Bank [indicate the name of the Bank, Address & Code] further hall have the fullest liberty without our consent and without affecting in order to vary any of the terms and conditions of the said Bid or to extend intractor(s) from time to time or to postpone for any time or from time to by OPTCL against the said contractor(s) and to forbear or enforce any or the said Bid and we shall not be relieved from our liability by reason or extension being granted to the said contractor(s) or for any forbearance TCL or any indulgence by OPTCL to the said contractor(s) or by any such under the law relating to sureties would, but for this provision, have the
6. This guarantee will not be discharg of the contractor(s).	ed due to the change in the name, style or constitution of the Bank and/or
	Bank [indicate the name of the bank, Address & Code] lastly antee during its currency except with the previous consent of OPTCL ir
	Bank (Name, Address & Code) further agree that this tour place of business at Bhubaneswar (indicate Name, Address & Code he State of Odisha.
" Notwithstanding anything	contained herein"
a) Our liability under the bank guarant only.	ntee shall not exceed Rs(Rupees in words)
b) This Bank guarantee shall be valid	up to
guaranteed amount or any part there	r < Mention Name, Address & Code> shall be liable to pay eof under this guarantee only if you serve upon us at Branch of and on or before
	paper form and Advice transmitted through SFMS with required details CICI Bank Bhubaneswar, IFSC Code ICIC0000061).
Dated, theDay of	

For	[Indicate name of Bank]		
Signatu	ure		
Full Na	me		
Design	ation		
Power	Of Attorney		
Dated.			
Seal of	the Bank		
WITNE	SS: (SIGNATURE WITH NAME AND ADDRESS)		
1.Signa	iture		
Full N	Full Name		
2. Sign	nature		
Full N	Jame		
N.B.:			
1.	Name of the Contractor.:		
2.	BG No & Date :		
3.	Amount (In Rs.):		
4.	Validity up to :		
5.	LOA No		
6.	Package No		
7.	Name, Address & Code of Issuing Bank:		

- 8. Name, Address & Code of Bhubaneswar Branch of the Issuing Bank:.....
- 10. The Bank Guarantee shall be accepted after getting SFMS advice as per details below.

Format for SFMS details

(The Unique Identifier for field 7037 is "OPTCL541405793")

SI. No	PARTICULARS	TYPE	DETAILS
1	Type of Bank Guarantee	Mandatory	Contract Performance
2	Currency & Amount	Mandatory	
3	Validity Period(from—to)	Mandatory	
4	Effective Date	Mandatory	
5	End date of lodgment of Claim	Mandatory	
6	Place of lodgment of claim	Mandatory	Bhubaneswar, Branch Name of Bhubaneswar Branch code of Bhubaneswar Branch Address at Bhubaneswar
7	Issuing Branch IFSC Code	Mandatory	
8	Issuing Branch name & address	Mandatory	
9	Name of applicant and its details	Mandatory	
10	Name of Beneficiary and its details	Mandatory	
11	Beneficiary's Bank/Branch and IFSC Code	Mandatory	ICICI Bank Ltd IFSC Code-ICIC0000061

12	Beneficiary's Bank/Branch name	Mandatory	ICICI Bank Ltd
	and address		Bhubaneswar Main Branch, Bhubaneswar
			biluballeswal
13	Sender to receiver information	Mandatory	
14	Purpose of Guarantee	Mandatory	Contract Performance
15	Reference/Description of the underlined tender/contract	Mandatory	LOA No

N.B.: To be Stamped in accordance with Stamp Act and the Non-Judicial Stamp Paper of appropriate value should be in the name of Issuing Bank

N.B.: To be Stamped in accordance with Stamp Act and the Non-Judicial Stamp Paper of appropriate value should be in the name of Issuing Bank

ANNEXURE-VIII

CHART SHOWING PARTICULARS OF EARNEST MONEY DEPOSIT FURNISHABLE BY TENDERERS

1.	Central and State Government Undertakings	Exempted
2.	All other inside & outside state units.	The amount of
		EMD as specified
		in the
		specification
		/Tender Notice in
		shape of bank
		guarantee /DD.

NB: - REFUND OF E.M.D.

- [a] In case of unsuccessful tenderers, the EMD will be refunded immediately after the tender is decided. In case of successful tenderer, this will be refunded only after furnishing of Composite Bank Guarantee referred to in clause No.19 of Section-II of this specification.
 - Suits, if any, arising out of EMD shall be filed in a court of law to which the jurisdiction of High Court of ODISHA extends.
- [b] Earnest Money will be forfeited if the tenderer fails to accept the letter of intent/purchase order, issued in his favour or revises the bid price[s] within the validity period of Bid.

ANNEXURE-IX

DATA ON EXPERIENCE

- [a] Name of the manufacturer.
- [b] Standing of the firm as manufacturer of equipment quoted.
- [c] Description of equipment similar to that quoted [supplied and installed during the last two years with the name of the organizations to whom supply was made].
- [d] Details as to where installed etc.
- [e] Testing facilities at manufacturer's works.
- [f] If the manufacturer is having collaboration with another firm, details regarding the same and present status.
- [g] A list of purchase orders, executed during last three years.
- [h] A list of similar equipments of specified MVA rating, voltage class, Impulse level, short circuit rating, Designed, manufactured, tested and commissioned which are in successful operation for at least two years from the date of commissioning with legible user's certificate. User's full complete postal address/fax/phone must be indicated. (Refer clause No.7 of the Part-I, Section-II of the specification).

Place:	
Date:	Signature of tenderer
	Name, Designation, Seal

ANNEXURE-X

SCHEDULE OF SPARE PARTS FOR FIVE YEARS OF NORMAL OPERATION & MAINTENANCE

SL.	Particulars	Quantity	Unit delivery rate	Total price
No				

Place:	
Date:	Signature of Tenderer
	Name, Designation, Seal

ANNEXURE-XI

SCHEDULE OF INSTALLATIONS.

Doted MIVA	Rated Voltage	Place of installation	Year of
Rated MVA		and complete postal	commissioning
		address	

Place: -	
Date	Signature of Tenderer:
	Name, Designation, Seal

ANNEXURE-XII

DEVIATION SCHEDULE.

Tenderer shall enter below particulars of his alternative proposal for deviation from the specification, if any.

A) Technical

(To be filled up by the tenderer as indicated in the excel sheet)

B) Commercial deviations.

(To be filled up by the tenderer as indicated in the excel sheet)

ANNEXURE - XIII

LITIGATION HISTORY

Year.	Award for o	Name of client, cause of litigation and matter in dispute	(current value in

D1	ac	م	• _	
_	7	_	_	

Date Signature of Tenderer:

Name, Designation, Seal

ANNEXURE-XIV

Certificate (to be furnished in bidder company's letter head)

I have read the clause regarding restrictions on procurement from a bidder of a country which shares a land border with India and on sub-contracting to contractors from such countries; I certify that this bidder is not from such a country or, if from such a country, has been registered with the Competent Authority and will not sub-contract any work to a contractor from such countries unless such contractor is registered with the Competent Authority. I hereby certify that this bidder fulfils all requirements in this regard and is eligible to be considered. [Where applicable evidence of valid registration by the Competent Authority shall be attached.]

		• .	
Δ 11+ ν	202200	aianat	177 7
Δ UII	ロロコスモロ	signate	JI V
		0-5-200	·,

Company seal

ANNEXURE-XV

AFFIDAVIT OF BIDDER (To be submitted in a non-judicial stamp paper of appropriate value)

BEFORE Sri/, Notary, At
<u>Affidavit</u>
WHEREAS the Odisha Power Transmission Corporation Ltd., Bhubaneswar(OPTCL) has
floated its Tender Noinviting bids
from eligible bidder to execute the work of
AND WHEREAS M/s(Briefly
"Bidder") has offered its bid onin response to the said Tender
Noof the OPTCL expressing its interest to execute the work as specified
<mark>therein.</mark>
AND WHEREAS the said Tender No of OPTCL requires the Bidder to solemnly
affirm the correctness of the document and information furnished in its bid, so offered to
OPTCL.
NOW WIDDEDONE
NOW THEREFORE, in response to the requirement, the Tender No
of OPTCL, and having been duly authorized by the Bidder, I Sri/ Mrs.
ged about years, Son/Daughter/Wife of Sri/Mrs
, At present working as of M/s
(The Bidder) do hereby solemnly affirm and state as follows:

- That I am competent and have been duly authorized by the Bidder M/s..... to swear this affidavit on its behalf.
- That the documents and information furnished by the Bidder in its bid offered in respect
- That in the event any document and information as furnished by the Bidder in response to the said Tender No of OPTCL is found/ considered by the OPTCL at any time as to be not correct/ wrong, the OPTCL shall be competent and at liberty without any show cause to the Bidder to terminate its contract/agreement With the Bidder, if any.
- 4. The OPTCL shall also be competent, without any reference to the Bidder, to black list the Bidder and debar the Bidder from participating in any other Tender of OPTCL pursuant to its consideration/ finding that the Bidder has furnished any incorrect/ wrong document and information tendered/made pursuant to Tender No of OPTCL.
- 5. That the affirmation made herein above is/are correct and true and nothing Stated herein is false.

T 1				-	-	
14	en	+++	10	\sim	h	T 7
101			10	(- 1	1 1/
- 0		CII		v.	\sim	. 7

DEPONENT ADVOCATE

PART - II

PRICE BID

1. PRICE:

(i) Bidders are required to quote their price(s) for goods offered indicating they are 'FIRM'

(ii) The prices quoted shall be FOR Destination only at the consignee's site/store inclusive of packing, forwarding, Freight & Insurance. In addition, the break-up of FOR Destination price shall be given as per schedule of Prices in Annexure-V of Section – III. The Bidders has to certify in the price bid that any implication of lower Tax and Input Tax Credit benefit as per anti-profiteering and other provisions under GST Laws, have been fully passed on to the Purchaser, while quoting the tender prices.

2. INSURANCE:

Insurance of materials/equipment, covered by the Specification should normally be done by the Suppliers with their own Insurance Company unless otherwise stated. The responsibility of delivery of the materials/equipment at destination stores/site in good condition rests with the Supplier. Any claim with the Insurance Company or Transport agency arising due to loss or damage in transit has to be settled by the Supplier. The Supplier shall undertake free replacement of equipment/materials damaged or lost which will be reported by the Consignee within 30 days of receipt of the equipment/materials at Destination without awaiting for the settlement of their claims with the carriers and underwriters.

3. CERTIFICATE FOR EXEMPTION FROM GOODS AND SERVICES TAX:

Offers with exemption from Goods and Services Tax shall be accompanied with authenticated proof of such exemption. Authenticated proof for this clause shall mean Photostat copy of exemption certificates, attested by Gazetted Officers of State or Central Government.

4. PROPER FILLING UP OF THE PRICE SCHEDULE:

The Bidders should fill up the price schedule (Annexure-V of Section-III) properly and in full. The tender may be rejected if the schedule of price is submitted in incomplete form as per clause-34 (ix) of Section-II of the Specification.

5. NATURE OF PRICE INDICATED IN SPECIFICATION SHALL BE FINAL.

The nature of price indicated in the Clause-13, Section – I of PART –I of the Specification shall be final and binding.

<u>SECTION – IV</u>

(A) TECHNICAL SPECIFICATION

FOR

HARDWARE FITTINGS & ACCESSORIES SUITABLE FOR POWER CONDUCTOR FOR (ACSR PANTHER, ACSR ZEBRA & ACSR MOOSE AND AAAC PANTHER, AAAC ZEBRA & AAAC MOOSE)

1.0 SCOPE

This Specification covers design, manufacture, assembly, testing at manufacturer's Works, supply and delivery of hardware fittings for string insulators suitable for use in 132 KV,220 KV and 400KV Over-head transmission lines ,Sub-Stations of OPTCL. The hard wares to be supplied shall be as per drawings to be approved by OPTCL AND CONFIRMING TO ISS AND IEC. The firm shall submit his drawings in line with the Specification of OPTCL indicating clearly all dimensions on the body of the drawing for approval of OPTCL and only after which the manufacturing shall be started.

The hardware offered, shall be complete with all components, which are necessary or usual for the efficient performance and satisfactory maintenance. Such part shall be deemed to be within the scope of contract. The AGS type clamps shall have inbuilt AGS clamps/PA Rods.

2.0 STANDARDS

The materials covered under this Specification shall comply with the requirement of the latest version of the following standards as amended up to date, except where specified otherwise.

1)	IS:2486 Part-II &	Insulator fitting for overhead power lines with a nominal voltage
	Ш	greater than 1,000 volts.
2)	IS:2121 Part I & II	Conductor & earth wire accessories for overhead power lines.
3)	IS:9708	Stock Bridge Vibration Dampers on overhead power lines.
4)	IS:2633	Method of testing of uniformity of coating on zinc coated articles
5)	IS:209	Specification for Zinc.
6)	BS:916	Specification for Hexagonal bolts and nuts.

3.0 MATERIALS AND DESIGN

Aluminum and aluminum alloys, malleable iron and forged steel, having required mechanical strength, corrosion resistance and machinability depending on the types of application for which accessories / fittings are needed, shall be employed. In manufacturer of the accessories / fittings, the composition of the aluminum alloys used shall be made available to Employer if required for verification.

The materials offered shall be of first class quality, workmanship, well finished and approved design. All castings shall be free from blow-holes, flaws, cracks of other defects and shall be smooth, close grained and true forms and dimensions. All machined surfaces should be free, smooth and well finished.

Metal fittings of specified material for conductor and string insulator fittings are required to have excellent mechanical properties such as strength, toughness and high resistance against corrosion. All current carrying parts shall be so designed and manufactured that contact resistance is reduced to the minimum.

All bolts, nuts, bolt-heads shall be the white worth's standard thread. Bolt heads and nuts shall be hexagonal. Nuts shall be locked in an approved manner. The treads in nuts and tapped holes shall be cut after galvanising and shall be well fabricated and greased. All other treads shall be cut before galvanising. The bolt treads shall be undercut to take care of increase in diameter due to galvanising.

All nuts shall be made of materials to Clause 4.8 of IS: 1367 (latest edition) with regard to its mechanical properties.

The general design of conductor and insulator fittings shall be such as to ensure uniformity, high strength, free from corona formation and high resistance against corrosion even in case of high level of atmosphere pollution.

All hooks, eyes, pins, bolts, suspension clamps and other fittings for attaching to the tower or to the line conductor shall be so designed that the effects of vibration, both on the conductor and the fittings itself, are minimized.

Special attention must be given to ensure smooth finished surface throughout. Adequate bearing area between fittings shall be provided and point or line contacts shall be avoided.

All accessories, clamps and hardware shall be free from cracks, shrinks, slender air holes, burrs or rough edges.

The design of the accessories, clamps and hardware shall be such as to avoid local corona formation or discharge likely to cause interference to Tele-transmission signals of any kind.

4.0 GALVANISING:

All ferrous parts of conductor accessories and insulator hardware shall be galvanized in accordance with IS: 2629-Recommended Practice for hot dip galvanizing of iron and steel or any other equivalent authorities' standards. The weight of zinc coating shall be determined as per method stipulated in IS: 2633 for testing weights, thickness and uniformity of coating of hot dip galvanized articles or as per any other equivalent authoritative standards. The zinc used or galvanization shall conform to grade Zn 98 of IS: 209. The galvanized parts shall withstand four (4) dips of 1 minute each time while testing uniformity of zinc coating as per IS: 2633.

Spring washers shall be electro galvanized.

ACCESSORIES FOR CONDUCTOR & GROUNDWIRE

5.0 MID SPAN COMPRESSION JOINTS (FOR AAAC & ACSR PANTHER, ZEBRA & MOOSE CONDUCTOR AND GROUND WIRE OF 7/3.15 Sq. mm)

The Mid-Span Joints for conductor and earth wire shall be of compression type. The conductor mid-span joints shall comprise of outer aluminum sleeve of extruded aluminum (99.5% purity) and inner sleeve HDG Steel. All filler plug shall also be

provided. The ground wire mid-span joints shall be of HDG steel. The sleeves shall be of circular shape suitable for compression into hexagonal shape.

The compression type mid-span straight joints shall be suitable for making joints in the ACSR/AAAC PANTHER, ZEBRA & MOOSE conductor or in the galvanized steel stranded ground wire.

The joints shall be so designed that when installed no air space is left within the finished joints. The joints shall have the conductivity as specified in relevant Clause.

The joints shall conform to IS: 2121 (latest edition) unless specified otherwise. The details of the joints both suitable for ACSR Conductors and ground wire are given in the technical particulars.

The inner and outer diameters and lengths of the offered joints before and after compression shall be clearly shown in the drawings.

6.0 VIBRATION DAMPER (FOR AAAC & ACSR PANTHER, ZEBRA & MOOSE AND GROUND WIRE (7/3.15))

Vibration Damper having 4 resonance frequency characteristic commonly called 4R Damper shall be offered. The Damper shall eliminate fatigue on the conductor due to vibration and damp out the vibration effectively so that no damage due to vibration is caused to conductor / ground wire/ string.

The dampers are proposed to be used at all tension locations and also at suspension locations. One or more dampers are proposed to be used on tension/suspension locations depending upon the span.

Bidder shall also recommend the number of damper required to effectively damp out conductor or ground wire vibration for different values of span lengths and the distance of fixation.

Vibration dampers shall be of approved design. The clamps of the vibration dampers shall be made of aluminum alloy, so designed as to prevent any damage while fixing on the conductor during erection or in continued operation. The fastening bolts should be approved by the Employer. The spring washers should be electro galvanized and of minimum 2 mm thickness. The messenger cable shall be made from high tensile strength steel strands in order to prevent subsequent drop of weight in service.

Clamping bolts shall be provided with self-locking nuts as designed to prevent corrosion of the threads. All ferrous parts including the messenger cable shall be hot dip galvanized. The end of the messenger cable shall be effectively sealed to prevent corrosion.

The vibration dampers and its attachment shall have smooth surface so that no corona occurs on them.

The clamps of the stock bridge vibration dampers shall be so designed that in case of loosening of the bolt or changing free parts of the clamp, it does not allow the damper to disengage from the conductor.

7.0 REPAIR SLEEVE

(FOR AAAC & ACSR PANTHER, ZEBRA & MOOSE CONDUCTOR AND GROUNDWIRE)

Compression type repair sleeves shall be offered to provide reinforcement for conductor with broken or damaged aluminum strands/galvanized steel ground wire broken in damaged steel strands. The repair sleeve shall be designed to make good a conductor of which not more than one- sixth $(1/6^{th})$ of the strands in the outermost layer and damaged or severed. The repair sleeves after compression should present a smooth surface.

8.0 TENSION CLAMPS (DEAD AND ASSEMBLY) FOR GOUND WIRE)

Compression type dead end assembly of G.S.S ground wire shall be required for use on the tension towers. The dead end assembly shall be supplied with complete jumper terminals, nuts and bolts suitable link pieces between the steel clevis and tower strain plates so as to provide sufficient flexibility not less than that of G.S.S ground wire and the tensile strength not less than 90% of that of the G.S.S ground wire.

The assemblies shall comprise of compression type dead end clamps and one anchor shackle made of forged steel. The entire assembly shall be hot dip galvanized.

One of bolt holding joint per terminal of dead end assemblies shall be kept sufficiently long and threaded and shall be provided with nuts, washers and locking nuts for fixing the flexible earthing bond between the dead-end clamp and tower structures.

9.0 **INSULATOR HARDWARES**

The insulator disc hardware and string assemblies to be offered by the tenderer shall be suitable to meet the requirement given in the specific technical particulars as detailed hereinafter.

Hardware for suspension and tension insulator shall be suitable for insulator with normal pin shank diameter of 20 mm. in case of tension string unit and 16mm for suspension string unit.

Each insulator string shall generally include the following hardware components.

Single Suspension Set.	Double Suspension Set.
a) Ball Hook	a) Ball Hook.
b) Tower side arcing horn	b) Socket clevis with R-Type security clip-3 Nos.
c) Socket Eye with R-Type security clip.	c) Yoke Plate-2 Nos.
d) Line side arcing horn.	d) Tower side arcing horns-2Nos.

e) Armour grip suspension clamps f) Cushion g) Armour Grip Helix	 e) Ball clevis – 2 Nos. f) Line side arcing homs-2 Nos. g) Clevis Eye. h) Armour Grip Suspension Clamp. i) Cushion j) Armour Grip Helix
Single Tension Set :	Double Tension Set :
a) Anchor Shackle.	a) Anchor Shackle.
b) Ball Eye.	b) Chain Link.
c) Tower side arcing horn.	c) Yoke Plate – 2 Nos. (Tower side-01 No. & Line Side-01 No.)
d) Socket Clevis with R-Type security clip.	d) Tower side arching horn.
e) Line side arcing horn	e) Ball Clevis – 2 Nos.
f) Compression type dead end clamp.	f) Socket Clevis with R-Type security clip – 2 Nos.
	g) Line side arcing horns.h) Compression type dead end clamps.i) Clevis

10.0 **CLAMP**

10.1 ARMOUR GRIP SUSPENSION CLAMPS

Armour Grip Suspension Clamp shall consist of 2 neoprene insert, one set of Armour rods made of aluminum alloy, two aluminum housing having inner profile matching with the profile of the Armour rods page and supporting strap made of aluminum alloy. The A.G. type suspension clamp shall be designed, manufactured and finished as to have a suitable shape without sharp edges at the end and to hold the respective conductor properly. It should, however, have sufficient contact surface to minimise damage due to fault current.

The A.G. Type suspension clamp shall permit the conductor to slip before the occurrence of failure of the conductor and shall have sufficient slip strength to resist the conductor tension under broken wire conditions. The clamp shall have slip strength of not less than 15 % of respective conductors.

10.2 **TENSION CLAMPS**

The Tension Clamps shall be made out of aluminum alloy and of compression type suitable for PANTHER/ZEBRA/MOOSE conductor for both AAAC & ACSR. The tension clamps shall not permit slipping or damage to failure of the complete conductor or any part thereof at a load less than 90% of the ultimate strength of conductor. The mechanical efficiency of tension / clamps shall not be affected by method of erection involving come / along or similar clamps or tension stringing operation during or after assembly and erection of

tension clamp itself. The tension clamp shall be of a design that will ensure unrestricted flow of current without use of parallel groove clamps. The clamps shall be as light as possible.

There shall be two pads with jumper cones (as per the enclosed drawing) for connection of two jumpers for the Tension clamps.

10.3 ARCING HORNS

Each hardware assembly shall have provision for attaching arcing horns of both adjustable and non/adjustable type across the suspension and tension strings or tower side. However each hardware assembly shall be provided with arching horn of fixed type on line side only.

10.4 UNIVERSAL JOINTING COMPOUND

BENDEX-HV' Universal jointing compound which is a chemically inert compound to be used as filler for the compression joints and dead end clamps to be supplied.

11.0 TESTS, TEST CERTIFICATE AND PERFORMANCE REPORTS

The fittings and accessories for the power conductor, insulator and hardwares shall be tested in accordance with IS: 2121, IS: 2486, IS: 9708 (For Vibration Dampers), BS: 916 for hexagonal bolts and nuts or any other authoritative equivalent standards. Type test, routine test certificates and performance reports are to be submitted by the bidder.

The Employer however, reserves the right to get all the tests performed in accordance with the relevant I.S. Specification as Acceptance Test in presence of Employer-s representatives.

The tenderer shall clearly state the testing facilities available in the laboratory at his Works and his ability to carry out the tests in accordance with this Specification. All the specified tests shall be carried out without any extra cost.

11.0 ACCEPTANCE TEST FOR POWER CONDUCTOR AND G.S.S. GROUND WIRE ACCESSORIES.

11.1 ACCEPTANCE TEST FOR POWER CONDUCTOR AND GROUND WIRE ACCESSORIES

- a) Visual & Dimensional verification.
- b) Failing load test.
- c) Slip strength test. (For clamps & vibration damper)
- d) Electrical resistance test.
- e) Resonance Frequency test (for vibration dampers)
- f) Fatigue test (for vibration damper)
- g) Mass pull off test (Slipping strength of messenger cable for vibration damper)
- h) Clamp bolt torque test (For vibration damper)
- i) Galvanizing test.
- j) Tests on P.A. Rod
- k) Tests on Locking Devices.

11.2 ACCEPTANCE TEST FOR HARDWARES

- I)Visual & Dimensional verification.
- m) Ultimate tensile/Mechanical strength test.
- n) Slip strength test. (For clamps)
- o) Electrical resistance test.
- p) Heating cycle test
- q) Breaking strength of full string assembly.
- r) Galvanizing test.
- s) Tests on P.A. Rod
- t) Tests on Locking Devices.

11.3 SPECIFIC TECHNICAL REQUIREMENTS FOR CONDUCTOR ACCESSORIES AND INSULATOR HARDWARES

CONDUCTOR	Panther/Zebra/Moose	G.S.S Ground wire
а) Туре	ACSR Panther/Zebra/Moose	Ground wire
b) Material	Aluminum conductor steel reinforced	Ground stranded steel wire
c) Strand & Wire diameter.	Panther/Al- 30/3mm steel-7/3mm	7/3.15mm
	Zebra/Al- 54/3.18mm steel- 7/3.18mm	
	Moose/ Al- 54/3.53mm steel- 7/3.53mm	
d) Weight per Km.	974/1622/2004 Kg per Km	426 kg per km
e) Overall diameter	21/28.62/ 31.7mm	9.4mm
f) D.C. Resistance at 20°C when corrected to standard weight	0.13750/ 0.06915 / 0.05552 Ohm/KM	3.375 Ohms/km
g) Minimum breaking load/ Ultimate tensile strength.	144/ 13289 / 16120 Kg	5710 kg
h) Maximum working tension at minimum temperature & 2/3 full wind.	3806/ 4325 Kg	1393kg
i) Maximum Sag at maximum temperature & no wind.	6120/ 9240mm	5150mm

DISC INSULATOR

(For suspension & tension Insulator strings of 132, 220 and 400 KV) accordingly hard ware fittings to be designed)

SI.	DESCRIPTION	Suspension	Suspension	Tension	Tension
No					

1	Electro Mechanical Strength of single insulator in KN	90 KN	120 KN	120KN	160KN
2	Type of Insulator	Ball & socket	Ball & socket	Ball & socket	Ball & socket
3	Size of ball & socket(mm)	16	16	20	20
4	Dimensions				
(a)	Disc diameter(mm)	255 mm	255 mm	280 mm	305 mm
(b)	Ball to ball spacing(mm)	145 mm	145 mm	145 mm	170 mm
(c)	Minimum Creepage distance of the single insulator-mm	430 mm	430 mm	430 mm	475 mm
5	Materials of shell	Porcelain	Porcelain	Porcelain	Porcelain

String arrangements for	Single	Single	Double	Double
132/ 220/ 400 KV:	Suspension	Tension	Suspension	Tension
No. of insulator discs.	9/14/24	10/15/25	2x9/2x14/	2x10/2x15/
			2x24	2x25
Length of string assembly	1672/ 2340	1851/3003	1837/	2132/3082
(mm)			2243	

LONG ROD INSULATOR

(For suspension & tension Insulator strings of 132 & 220 KV) accordingly hard ware fittings to be designed)

l. No	DESCRIPTION	Suspension	Tension
1	Type of Insulator	Ball & socket	Ball & socket
2	Size & designation of ball &	16 mm, Alt-B	20 mm, Alt-B
	socket and standard to	IS-2486-II	IS-2486-II
	which it will conform (mm)		
3	No of insulator per string	One	One
4	Outside dia of the LRI (mm)	200	205
5	Creepage distance of	4000	4300
	insulator (mm)		
6	Mechanical strength of	90 KN	120 KN
	single LRI (KN)		

Sl. No	DESCRIPTION	Suspension	Suspension	Tension
1	Type of Insulator	Ball & socket	Ball & socket	Ball & socket
2	Size & designation of ball & socket and standard to which it will conform (mm)	16 mm	20 mm	20 mm
3	No of insulator per string	Two	Two	Two
4	Largest sheds diameter (mm)	210	210	215
5	Creepage distance of insulator (mm)	6125	6450	7130
6	Mechanical strength of single LRI (KN)	90 KN	120 KN	160 KN

132 KV Long Rod insulator					
Type of string	Size of long rod (mm)/ Unit	Minimum creepage distance (mm)	No. of unit	Electromecha nical strength of insulator (KN)	
Single Suspension	180x1450	3625	1	90 KN	
Double Suspension			2	2x90 KN	
Single Tension	205x1450	4300	1	120 KN	
Double Tension			2	2x120 KN	
220 KV Long Rod insula	ator				
Type of string	Size of long rod (mm)/ Unit	Minimum creepage distance (mm)	No. of unit	Electromec hanical strength of insulator (KN)	
Single Suspension	210x2175	6450	2	120 KN	
Double Suspension			4	2x120 KN	
Single Tension	215x2550	7130	2	160 KN	
Double Tension			4	2x160 KN	

GENERAL REQUIREMENT FOR HARD WARE FITTINGS FOR POWER CONDUCTOR & GROUND WIRE:

1) ACCESSORIES

A) MID-SPAN COMPRESSION JOINTS

(SUITABLE FOR AAAC/ ACSR PANTHER, ZEBRA & MOOSE CONDUCTOR)

	Suitable for AAAC/ ACSR Panther/ Zebra/ Moos		
i) Type	Compression		
ii) Material			
a) Outer sleeve	Extruded Aluminum		
b) Inner sleeve	Steel (galvanized)		
iii) Dimension of Compression joint for	Before Compression	After compression	
Aluminum part.	Outer dia: 38mm Inner Dia: 23mm Minimum length: 610 mm Minimum weight 1.2kg (approx.)	Adjacent side: 32mm Diagonal size: 37 mm	
iv) Dimension of compression joint for Steel Part	Outer dia: 18 mm Inner Dia: 9.3 mm Minimum length: 203 mm Minimum weight 0.28 kg approx.)	Adjacent side: 15.1 mm Minimum: 10 mm	
v) Minimum failing load.	95% of ultimate tensile strength	n of conductor	
vi) Electrical resistance 20 Deg. C	75% of measured resistance of length of conductor.	of the equivalent	
vii) Galvanising :			
(a) Ferrous Parts.	Hot-dip galvanized (HDG)		
(b) No. of dips 4 dips for 1 minute withstand.	4 dips		
viii) Minimum Corona formation voltage	110% of maximum line to ground voltage		

(B) VIBRATION DAMPERS

(SUITABLE FOR AAAC/ ACSR PANTHER, ZEBRA & MOOSE CONDUCTOR:

- i) Type: 4R Stock Bridge Type
- ii) Distance between conductors: 74.5 mm. & axis of the Vibration Damper.
- iii) Messenger Cable: 130 Kg/mm sq. quality (19 strands)
- iv) Bolt size: 16 mm. (dia.)
- v) Slip strength of messenger Cable: 500 Kg
- vi) Mass pull-of: As per I.S.S.

c) **REPAIR SLEEVES**

(SUITABLE FOR AAAC/ ACSR PANTHER, ZEBRA & MOOSE CONDUCTOR)

	Suitable for ACSR panther/Zebra/ Moose
i) Type	Compression
ii) Material	Extruded aluminum.
iii) Min. failing load	95% of UTS of conductor.
iv) Length	241/279 mm.
v) Dimension :	
a) After compression	
(i) Adjacent side	21 mm
b) Before Compression	
(i) Outer diameter 38/48 mm.	21 mm
(ii) Inner diameter 23/40 mm	11.5 mm
vi) Electrical resistance AT 20° C	Not more than 75% of the resistance of equivalent length of conductor.
vii) Galvanizing:	Hot – dip galvanized
a) Ferrous parts	
b) No. of dips for one-minute stand	4 dips

D) INSULATOR HARDWARES (BOTH SUSPENSION AND TENSION)

String Hardware: Material and strength

Description of item	Material	UTS
i)Bolt hook	Forged Steel	9,000/ 11,500/16,500 Kgs
		(90 KN/120KN/160KN)
ii) Anchor Shackle		11,500/16,500 Kgs
		(120 KN/160 KN)
iii) Socket Eye Horn Holder.		9,000/11,500 /16500Kgs
		(90 KN/120 KN/160 KN)
iv) Socket Clevis		9,000/11,500/16,500 Kgs
v) Ball Clevis		9,000/11,500/16,500 Kgs
vi) Clevis Eye		9,000/11,500/16,500 Kgs
vii) Socket Eye		9,000/11,500/16,500 Kgs

viii) Bottom / Top Yoke plate			
Double Suspension	Double Suspension Mild steel		16,500 Kgs
Double Tension	Mild steel	16, 500 Kgs	
ix) Arcing Horn	Mild steel		
x) Suspension Clamp	Aluminum Alloy & Neoprene		
xi) Tension Clamp	All alloy & Steel		11,500/16,500 kgs
xii) Ball Pin	High tensile forged steel (HDG)		90 % of UTS of conductor
xiii) Security clip	Brass (R-Type)		

Minimum failing load String (KN)

Single Suspension	9,000/11,500/16,500 Kgs
Single Tension	11,500/16,500 kgs
Double Suspension	2 time the UTS of Single suspension
Double Tension	2 time the UTS of Single Tension

B) HARDWARE FITTINGS SUITABLE FOR AAAC CONDUCTOR

The Hardware should be suitable for above type of conductor and as per drawing & specification marked on the body of the drawing.

All 'D' shackles should be perfect in manufacturing and shall be subjected to "X-Ray test at the time of inspection. All the hardware & fittings should be manufactured strictly in accordance with ISS. In case of deviation in technical specification, the same shall be duly approved from the Sr. general Manager [C.P.C.], OPTCL.

1. Dimensions of insulator string along with hardware fitting.

The various limiting dimensions of the single suspension / double suspension and single/double tension hardware fittings shall be as per the sketches.

- 2. Interchangeability.
 - 2.1 The hardware for insulator strings with disc insulators together with ball and socket fittings shall be standard design, so that this hardware are interchangeability with each other and suitable for use with disc insulators of any make conforming to relevant Indian/International standard.
 - 2.2 The hardware fittings offered shall be suitable for employment of hot line maintenance techniques so that usual hot line operations can be carried out with ease, speed and safety. The technique adopted for hot line maintenance shall be generally bare hand method and hot stick method. The Bidder should clearly establish in the bid, the suitability of his fittings for hot line maintenance.

- 2.3 The line side yoke plate shall have a notch and a working hole of suitable size to facilitate the hot line working. The design of corona control ring or grading ring shall be such that it can be easily replaced by employing hot line maintenance technique.
- 2.4 Ball and socket designation.

The dimensions of the ball and socket shall be 20mm wherever 120 and 160 KN insulators are used and 16 mm when 90 KN insulators are used. The designation should be in accordance with the standard dimensions stated in IS-2486(Part-II)/ IEC 120. The dimensions shall be checked by appropriate gang after galvanizing only.

- 3. Security clips and split pins.
- 3.1 Security clips for use with ball and socket coupling shall be R-shaped, hump type which provides positive locking of the coupling as per IS-2486 (Part-III)/IEC-372. The legs of the security clips shall be spread after assembly in the works to prevent complete withdrawal from the socket. The locking device shall be resilient, corrosion resistant and of suitable mechanical strength. There shall be no risk of the locking device being displaced accidentally or being rotated when in position. Under no circumstances shall the locking devices allow separation of fittings.
- 3.2 The hole for the security clip shall be countersunk and the clip shall be of such design that the eye of clip may be engaged by a hot line clip puller to provide for disengagement under energised conditions. The force required to pull the security clip into its unlocked position shall not be less than 50 N (5 Kg.) or more than 500 N (50 Kg.)
- 3.3 Split pins shall be used with bolts and nuts. The Bidder must note that 2.5% extra fasteners are to be supplied without any extra cost to the Employer, to deal with losses during erection.

4. Arcing horn.

- 4.1 The arcing horn shall be either ball ended rod type or tubular type and shall be formed from galvanized mild steel and of approved types. The arcing horns shall be attached in an approved manner to all suspensions and tension insulator sets. The horns shall be attached to the insulator fittings, but not directly to conductor clamps or to the caps of insulator units. The design of the arcing horns shall be such as to reduce as far as reasonably possible, damage to the line conductors, clamps, insulators strings and arcing horns themselves under all flashover conditions. The general shape and method of attachment of the live end arcing horn shall also not restrict the replacement of insulators under live line condition.
- 4.2 The total effective arcing distance shall be 2130 mm 220 kV.

II) CLAMPS

	SINGLE SUSPENSION STRING	SINGLE TENSION STRING	DOUBLE SUSPENSION STRING	DOUBLE TENSION STRING
i) Type	AGS Type	Compression Type	AGS Type	Compression Type
ii) Material	Aluminum Alloy and neoprene	Aluminum Alloy and Steel	Aluminum Ally and Neoprene	Aluminum Alloy and Steel
ii) Minimum slip strength	Not less than 15%	90% of UTS of conductor	Not less than 15% of UTS of conductor	90% of UTS of conductor
iv) Minimum failing load (kg)	9,000/11,500	90% of UTS of conductor	9,000/11,500	90% of UTS of conductor

III) Suspension assembly: General (AGS Type with AGS Clamps)

- 1. The suspension assembly shall be suitable for 132kv ACSR Panther Conductor (30+7/3.0mm), 220 KV ACSR Zebra Conductor(54+7/3.18mm), ACSR Moose Conductor (54+7/3.53mm), AAAC Panther conductor (37/3.15mm), AAAC Zebra Conductor (37/4.0mm) & AAAC Moose Conductor (61/3.55mm).
- 2. The suspension clamp along with standard preformed Armour rods or Armour grip suspension clamp set shall be designed to have maximum mobility in any direction and minimum moment of inertia so as to have minimum stress on the conductor in the case of oscillation of the same.
- 3. The suspension clamp along with Armour grip suspension clamp set shall have slip strength between **20 to 29 KN 37/4.00 mm**² and as per ISS for other conductors. The tightening torque for the bolts, wherever applicable shall be specified by the manufacturer to achieve the above slip strength.
- 4. The suspension assembly shall be designed, manufactured and finished to give it a suitable shape, so as to avoid any possibility of hammering between suspension assembly and conductor due to vibration. The suspension assembly shall be smooth without any cuts, grooves, abrasions, projections, ridges or excrescence which might damage the conductor.
- 5. The suspension assembly/clamp shall be designed so that it shall minimize the static and dynamic stresses developed in the conductor under various loading conditions as well as during wind induced conductor vibrations. It shall also withstand power arcs and have required level of corona/RIV performance.

IV) Suspension assembly: Armour Grip Clamp

- 1. The Armour grip suspension clamp shall comprise of retaining strap, support housing, elastomer inserts with aluminum reinforcements and AGS preformed rod set.
- 2. Elastomer insert shall be resistant to the effects of temperature up to 85 deg. C, ozone, Ultraviolet radiation and other atmospheric contaminants likely to be encountered in service. The physical properties of the elastomer shall be of approved standard. It shall be electrically shielded by a cage of AGS preformed rod set. The elastomer insert shall be so designed that the curvature of the AGS rod shall follow the contour of the neoprene insert.
- 3. The AGS preformed rod set shall be as detailed above in general except that the length of the AGS preformed rods shall be such that it shall ensure sufficient slipping strength and shall not introduce unfavorable stress on the conductor under all operating conditions.

V) Fasteners: (Bolts, Nuts & Washers)

- 1. All bolts and nuts shall conform to IS-6639 1972. All bolts and nuts shall be Hot DIP galvanized. All bolts and nuts shall have hexagonal heads, the heads being truly concentric, and square with the shank, which must be perfectly straight.
- 2. Bolts up to M16 and having length up to ten times the diameter of the bolt should be manufactured by cold forging and thread rolling process to obtain good and reliable mechanical properties and effective dimensional control. The shear strength of bolt for 5.6 grade should be 310 Mpa minimum as per IS-12427. Bolts should be provided with washer face in accordance with IS-1363 Part-I to ensure proper bearing.
- 3. Fully threaded bolts shall not be used. The length of the bolt shall be such that the threaded portion shall not extend into the place of contact of the component parts.
- 4. All bolts shall be threaded to take the full depth of the nuts and threaded enough to permit the firm gripping of the component parts but not further. It shall be ensured that the threaded portion of the bolt protrudes not less than 3 mm and not more than 8 mm when fully tightened. All nuts shall fit and be tight to the point where shank of the bolt connects to the head.
- 5. Flat washers and spring washers shall be provided wherever necessary and shall be of positive lock type. Spring washers shall be electro-galvanized. The thickness of washers shall conform to IS-2016-1967.
- 6. The bidder shall furnish bolt schedules giving thickness of components connected, the nut and the washer and the length of shank and the threaded portion of the bolts and size of holes and any other special details of this nature.
- 7. To obviate bending stress in bolt, it shall not connect aggregate thickness more than three time its diameter.
- 8. Bolts at the joints shall be so staggered that nuts may be tightened with spanners without fouling.
- 9. Fasteners of grade higher than 8.8 are not to be used and minimum grade for bolts shall be 5.6.

GENERAL:

- 1. All ferrous parts including fasteners shall be hot dip galvanized, after all machining has been completed. Nuts may however be tapped (threaded) after galvanizing and the threads oiled. Spring washers shall be electro-galvanized. The bolt threads shall be undercut to take care of the increase in diameter due to galvanizing. Galvanizing shall be done in accordance with IS-2629-1985 and shall satisfy the tests mentioned in are 2633-1986. Fasteners shall withstand four dips while spring washers shall withstand three dips of one-minute duration in the standard Preece test. Other galvanized materials shall be guaranteed to withstand at least six successive dips each lasting one minute under the Standard Preece test for galvanizing.
- 2. The zinc coating shall be perfectly adherence of uniform thickness, smooth, reasonably bright, continuous and free from imperfections such as flux, ash, rust stains, bulky white deposits and blisters. The zinc used for galvanizing shall be of grade Zn 99.95 as per IS 209-1979.
- 3. Pin balls shall be checked with the applicable "G)" gauges in at least two directions, one of which shall be across the line of die flashing and the other 90 deg. to this line. 'NO GO' gauges shall not pass in any direction.
- 4. Socket ends, before galvanizing shall be of uniform contour. The bearing surface of socket ends shall be uniform about the entire circumference without depressions or high spots. The internal contours of socket ends shall be concentric with the axis of the fittings as per IS 2486/IEC-120. The axis of the bearing surfaces of socket ends shall be coaxial with the axis of the fittings. There shall be no noticeable tilting of the bearing surfaces with the axis of the fittings.
- 5. All current carrying parts shall be so designed and manufactured that contact resistance is reduced to minimum.
- 6. Welding of aluminum shall be by inert gas shielded tungsten are or inert gas, shielded metal arc process. Welds shall be clean, sound, smooth, and uniform without overlaps, properly fused and completely sealed. There shall be no cracks, voids incomplete penetration, incomplete fusion, under-cutting or inclusions Porosity shall be minimized so that mechanical properties of the aluminum alloys are not affected. All welds shall be properly finished as per good engineering practices.

Electrical Design:

The heavy duty suspension, and heavy duty tension insulator sets shall all comply with the technical requirements of schedule C and ISS and IEC and satisfy the test requirements stated in Section-7.

Mechanical design:

The mechanical strength of the insulators and insulator fittings shall be as stated in Schedule-C

The design shall be such that stresses due to expansion and contraction in any part of the insulator shall not lead to the development of defects.

Insulating material shall not engage directly with hard metal. All fixing materials shall be of approved quality, shall be applied in an approved manner and shall not enter into chemical action with the metal parts or cause fracture by expansion in service. Where cement is used as a fixing medium, cement thickness shall be as small and even as possible and proper care shall be taken to correctly center and locate the individual parts during cementing.

TECHNICAL SPECIFICATION FOR DESIGN, SUPPLY AND TESTING OF HARD WARE FITTINGS

Type tests:

The following type tests shall be conducted on hardware fittings.

A. <u>On suspension hardware fittings only.</u>

- (a) Magnetic power loss test.
- (b) Clamp slips strength vs. torque
- (c) Mechanical strength test.
- (d) On one test on elastomer.

B. <u>On Tension hard ware fittings only.</u>

Electrical resistance test for Dead end assembly IS 2486 (Part-I) 1971

- (a) Heating cycle test for dead end assembly. -do-
- (b) Slip strength test for dead end assembly. IS 2486 (Part-I)
- (c) Mechanical strength test.

C. On both suspension and tension hardware fittings.

(a) Visual examination. IS-2486 (Part-I) 1971

(b) Verification of dimension. -do-

(c) Galvanizing / electroplating test. -do-

(d) Mechanical strength test of each component

(Including corona control ring/grading ring and arcing horn)

- (e) Mechanical strength test of welded joint.
- (f) Mechanical strength test for corona control ring/

Grading ring and arcing horn.

BS-3288 (Part-I)

- (g) Test on locking device for ball and socket coupling. IEC 3721984
- (h) Chemical analysis, hardness tests, grain size, inclusion rating and magnetic particle inspection for forging/casting.

D. <u>On suspension hardware fittings only.</u>

- (a) Clamp slips strength over as torque test for suspension clamp.
- (b) Shore hardness test of elastomer cushion for AG suspension clamp.
- (c) Bend test for rod set. IS-2121 (Part-I)
- (d) Resilience test for Armour rod set. -do-
- (e) Conductivity test for Armour rod set. -do-

E. On Tension hardware fittings only.

(a) Slip strength test for dead end assembly. IS-2121 (Part-I)

All the acceptance tests stated at clause shall also be carried out on composite insulator unit, except the eccentricity test at clause. In addition to these, all the acceptance tests indicated in IEC 1109 shall also be carried out without any extra cost to the employer.

F. For hardware fittings.

- (a) Visual examination. IS-2121 (Part-I)
- (b) Proof & test.

G. Tests on Conductor Accessories

H. Type tests

- 1) Mid span Compression Joint for Conductor and Earth wire
 - (a) Chemical analysis of materials.
 - (b) Electrical resistance tests. IS-2121 (Part-II) 1981 clause 6.5 & 6.6
 - (c) Heating cycle test.

-do-

(d) Slip strength test.

- -do-
- (e) Corona extinction voltage test (dry)
- (f) Radio interference voltage test (dry)

2) Repair Sleeve for Conductor

- a) Chemical analysis of materials.
- b)Electrical resistance tests.

IS-2121 (Part-II) 1981 clause 6.5 & 6.6

-do-

(c) Heating cycle test.

- -do-
- (d) Slip strength test/ Failing Load test
- (e) Corona extinction voltage test (dry)
- (f) Radio interference voltage test (dry)
- (g) Visual Examination.
- (h) Verification of Dimensions

3) <u>Vibration Damper for Conductor.</u> (IS 9708-1993, IS 2633-1986)

- (a) Visual Examination
- (b) Verification of Dimensions
- (c) Resonance Frequency test
- (d) Dynamic Characteristics test
- (e) Damper efficiency test

- (f) Clamp slip test (Before Fatigue test)
- (g) Fatigue test (for 10 million cycle)
- (h) Mass pull off test
- (i) Clamp bolt torque test
- (j) Galvanising test (Uniformity of Zinc coating)
- (k) Magnetic power loss test

Characteristics as per IS:398 Part _II/1976

ACSR Panther 30+7/3.00 mm

Area-212.1 Sq.mm Outer Diameter-21mm Weight in Kg-973.1 Kg per Km Brkd – 9241.9 Kg

ACSR Zebra 54+7/3.18 mm

Area-428.9 Sq.mm Outer Diameter-28.62 Weight in Kg-1620 Kg per Km Brkd in Kg- 13466.4

ACSR Moose 54+7/3.53 mm

Area-528.5 Sq.mm Outer Diameter-31.77 mm Weight in Kg-1996.2 Kg per Km

AAAC Panther 37/3.15 mm

Area-288 Sq.mm Outer Diameter-22.05mm Brkd – 84.71KN

AAAC Zebra 37/4.0 mm

Area-465 Sq.mm Outer Diameter-28mm Brkd in Kg- 136.38KN

AAAC Moose 61/3.55 mm

Area-604 Sq.mm
Outer Diameter-31.95 mm
Weight in Kg-1666.00 Kg per Km
Brkd in – 167.99 KN

SCHEDULE OF GUARANTEED TECHNICAL PARTICULARS

HARDWARE FITTINGS AND ACCESSORIES FOR AAAC/ ACSR PANTHER/ZEBRA/MOOSE CONDUCTOR

Α	HARDWARES	SUSPENSION	TENSION
i	Maker's name, Address and Country		
ii	Size and designation of ball and socket with standard specification to which conforming	16mm as per IS 2486	20mm as per IS 2486
iii	Material		
a)	Anchor shackle	NA	Forged steel Galvanized
b)	Chain Link	NA	Forged Steel Galvanized

c)	Ball hook / Ball Link (HH)	Forged Steel Galvanized			rged Steel alvanized
d)	Socket Eye (HH)	Forged Steel Gal		NA	
e)	Ball Clevis	Forged Steel Gal	vanized		rged Steel alvanized
f)	Socket Clevis	Forged Steel Gal	vanized		rged Steel alvanized
g)	Yoke Plate	Mild Steel Galv	anized		1ild Steel alvanized
h)	Arcing Horn	Mild Steel Galv	anized		1ild Steel alvanized
I)	Clamp Suspension	A.G.S. Clan	пр		NA
J)	Dead End/Cross arm strap	NA			NA
k)	Dead end clamp (Compression)	NA		Extruded Aluminum Alloy	
iv	Standard specification to which the Hardware conform	IS 2486, IS: 2004,IS:617, IS-2633, & IS-733			IS-733
V	Standard specification to which conforming	IS: 2486			
vi	Galvanizing				
a)	Ferrous parts	Ho	t Dip Galva	inized	
b)	Spring washers	Ele	ctro Galva	nized	
c)	Quality of zinc used		99.5%		
d)	Number of dips which the clamp can withstand	4/ 1 minute dips			
vii	Standard to which conforming	IS 2633			
Viii	Reference to drawing No.				
ix	Minimum failing load in kg	For AAAC/ ACSR Panther (132 KV)	For AA ACSR Ze (220 k	ebra	For AAAC/ ACSR Moose (220 KV)

С	SUSPENSION CLAMPS	AAAC/ ACSR Panther	AAAC/ ACSR Zebra	AAAC/ ACSR Moose		
ix	Make of bolts and nuts used					
viii	Reference to type tests and other tests reports attached					
	b. Electrical resistance	Not more than 75% of equivalent length of conductor				
	a. Results of heating cycle test carried out					
vii	Electrical Conductivity					
vi	Standard to which conforming	IS 2633				
d)	Number of dips which the clamp can withstand	4/ 1 minute dips				
c)	Quality of zinc used	99.5%				
b)	Spring washers	Electro Galvanized				
a)	Ferrous parts	Hot Dip Galvanized				
V	Galvanising					
iv	Slipping strength	95% of UTS of Co	nductor			
iii	Breaking Strength	95% of UTS of Co	nductor			
ii	Material	Ext. Al. Alloy/ Ext	. Al.			
i	Туре	Compression typ	e tension clamp			
В.	TENSION CLAMPS	Suitable for AAA Moose	AC/ ACSR Pantho	er, Zebra &		
d)	For Double Suspension Hardware Fittings	90 KN	120 KN	120 KN		
c)	For Single Suspension Hardware Fittings	90KN	120KN	120KN		
b)	For Double Tension Hardware Fittings	120 KN	160 KN	160 KN		
a)	For Single Tension Hardware Fittings	120 KN	160 KN	160 KN		

i	Туре	AGS Type					
ii	Type of material used for retaining rod for AGS assembly giving reference of ISS	6061/		Aluminum Alloy 6061/ Equivalent		Aluminum Alloy 6061/ Equivalent	
iii	Minimum tensile strength of retaining rod material	35 kg/mm ²		35 kg/	mm²	35 k	g/mm²
iv	Chemical composition of retaining rod material	As per IS:73	3	As per	IS:733	As p	er IS:733
V	Electrical conductivity of Armour Rod material (in percentage of the conductivity of IACS i.e. International Annealed Copper Standard				Not less than 40% of IACS		less than of IACS
vi	Slipping strength of cushioned suspension assembly	8% to 15% of UTS of Conductor	UTS of		to 29 KN 20 to 29 H		o 29 KN
vii	Breaking strength of suspension Clamp	9000kgf 12000k		kgf 12000kgf		00kgf	
viii	Physical properties of neoprene cushion						
a)	Minimum Tensile Strength	2000 psi		2000 psi		200	0 psi
b)	Minimum ultimate Elongation	300%		300%		3009	%
ix)	Ageing (guaranteed life of the assembly)	40 years		40 yea	rs	40 y	ears
x)	Hardness	65 to 80 A		65 to 8	80 A	65 t	o 80 A
D	Mid-Span Compression Joints	Panther		•	Zebra	•	
		AAAC	ACS	R	AAAC		ACSR
i	Туре		Co	ompressi	on Type		•
ii	Suitable for	AAAC	ACS	R	AAAC		ACSR
		Panther	Pant	ther	Zebra		Zebra
iii	Materials						
a	Outer Sleeve	Ex. Al. Alloy	Ex. Al.		Ex. Al. Alloy		Ex. Al.
b	Inner Sleeve	N.A.	Galvanized Steel		N.A.		Galvaniz e d Steel
iv	Outer Sleeve	_					

E	Compression type Tension clam Galvanized Stranded Steel Wire		end Assembly	for 7/3.15m	m
xi v	length of conductor	Not more than 75% of equivalent length of conductor			
•••	Resistance as percentage of measured resistance of equivalent	NI ₀ t	ove the 75% of a	auivalant laa	rth of
xi ii	Conductivity of Compression joint expressed as percentage of conductivity of cable	100% of equivalent length of conductor			
xi i	expressed as percentage of UTS of conduct	95%			
xi	expressed as percentage of UTS of conductor Breaking strength of mid span joint	95%			
<u>x</u>	Standard to which conforming Slipping strength of mid span joint			2633	
d	Number of dips which the clamp can withstand			nute dips	
С	Quality of zinc used		99	.5%	
a b	Spring washers			Balvanized	
ix	Galvanizing Ferrous parts		Hot Di	p Galvanized	
b	Galvanized Steel (kg)	N.A.	0.295	N.A.	0.410
a	Aluminum (kg)	1.2	1.2	2.032	2.032
viii	Weight of Sleeve				
b	After compression (mm)	N.A.	230	N.A.	273
a	Before compression (mm)	N.A.	203	N.A.	241
vii	Length of Inner Sleeve				
b	Flat to Flat After compression (mm)	N.A.	15.1	N.A.	16.1
a	Outer Dia. Before compression (mm)	N.A.	Ø 18	N.A.	Ø 19.2
vi	Inner Sleeve				
b	After compression (mm)	655	660	760	768
a	Before compression (mm)	610	610	711	711
v	Length of Outer Sleeve				
b	Flat to Flat After compression (mm)	32	32	40	40
a	Outer Dia. Before compression (mm)	Ø 38	Ø 38	Ø 48	Ø 48

i	Materials	Forged steel
ii	Size	As per drawing
iii	Suitable for ground wire	Yes (7/3.15)
iv	Weight in kg	3.69
V	Minimum failing load	70 KN
vi	Galvanising	
а	Ferrous parts	Hot Dip Galvanised
b	Spring washers	Electro Galvanized
С	Quality of zinc used	99.5%
d	Number of dips which the clamp can withstand	4/ 1 minute dips
vii	Standard to which conforming	IS 2486 and IS 2633

F	Vibration Damper Total weight of the damper (Kg)	For AAAC/ ACSR PANTHER, ZEBRA & MOOSE				
i		4.5 Approx.				
		Left	Right			
ii	Weigh of each damper mass (kg)	1.6	2.2			
iii	Resonance frequencies					
	1. First frequency (Hz)	12± 1	18± 2			
	2. Second frequency (Hz)	28± 2	36±2			
iv	Dimensions of each damper mass	55 φ x 165	60 φ x 195			
V	Material of :					
	1. Damper mass	Cast iron hot dips Galv	vanized.			
	2. Messenger cable.	High tensile Galvanize	d steel wire.			
vi	Galvanising					
а	Ferrous parts	Hot Dip Galvanized				
b	Spring washers	Electro Galvanized				
С	Quality of zinc used	99.5%				

d	Number of dips which the clamp can	4/1 minute dips
ď	withstand	4/ I minute dips
	Withstand	
vii	Standard to which conforming	IS 2486 and IS 2633
viii	No of strands in messenger cable	19
	strands	
ix	Lauratio of massanger cable strands	9- 11
IX	Lay ratio of messenger cable strands	9- 11
х	Min tensile strength of messenger	135
	cable (kg /sq. mm)	
хi	Mass pull – off strength (KN)	5
	Clamping targue (KCM)	7
xii	Clamping torque (KGM)	/
xiii	Slipping strength of the damper clamp	
	1.Before fatigue test (KN)	2.5
	2. After fatigue test (KN)	2
	2. Arter ratigue test (KIV)	
xiv	Magnetic power loss per vibration	1 watt at 500 amps
	damper (Watts)	
xv	Min. corona extinction voltage under	154
	dry conditions (KV)	
xvi	Radio interference voltage under	Below 1000
	conditions 1 MHZ, AT 154 KV	2000
	(Microvolt)	
	(IVIICIOVOIL)	
xvii	Percentage variation in reactance after	20
	fatigue test in comparison with that	
	before the fatigue test (%)	

_	Mid-span Compressions Joints	Panther		Zebra	
D		AAAC	ACSR	AAAC	ACSR
i	Туре	Compression Type			
ii	Suitable for	AAAC	ACSR	AAAC	ACSR
		Panther	Panther	Zebra	Zebra
iii	Materials				
a	Outer Sleeve	Ex. Al. Alloy	Ex. Al.	Ex. Al. Alloy	Ex. Al.

b	Inner Sleeve	N.A.	Galvanized Steel	N.A.	Galvanize d Steel	
iv	Outer Sleeve					
a	Outer Dia. Before compression (mm)	Ø 38	Ø 38	Ø 48	Ø 48	
b	Flat to Flat After compression (mm)	32	32	40	40	
V	Length of Outer Sleeve					
a	Before compression (mm)	610	610	711	711	
b	After compression (mm)	655	660	760	768	
vi	Inner Sleeve					
a	Outer Dia. Before compression (mm)	N.A.	Ø 18	N.A.	Ø 19.2	
b	Flat to Flat After compression (mm)	N.A.	15.1	N.A.	16.1	
vii	Length of Inner Sleeve					
a	Before compression (mm)	N.A.	203	N.A.	241	
b	After compression (mm)	N.A.	230	N.A.	273	
viii	Weight of Sleeve					
a	Aluminum (kg)	1.2	1.2	2.032	2.032	
b	Galvanized Steel (kg)	N.A.	0.295	N.A.	0.410	
ix	Galvanizing		II. t D	: C-1:-		
a	Ferrous parts			ip Galvaniz		
b c	Spring washers Quality of zinc used			Galvanized 9.5%		
d	Number of dips which the clamp can			inute dips		
•	withstand Standard to which conforming		TC	5 2633		
X	Slipping strength of mid span joint		10	2033		
xi	expressed as percentage of UTS of conductor			95%		
xii	Breaking strength of mid span joint expressed as percentage of UTS of conduct	95%				
xiii	Conductivity of Compression joint expressed as percentage of conductivity of cable	100% of equivalent length of conductor				
xiv	Resistance as percentage of measured resistance of equivalent length of conductor	Not more than 75% of equivalent length of conductor				
E	Repair Sleeves		C/ACSR nther	AA	AC/ACSR Zebra	

i	Туре		Compress	sion type		
ii	Suitable for	AAAC Panther	ACSR Panther	AAAC Zebra	ACSR Zebra	
iii	Outside diameter or length of sleeve					
a	Before compression (mm)	Ø 38	Ø 38	Ø 48	Ø 48	
b	After compression Flat to Flat (mm)	32	32	40	40	
iv	Length of Sleeve					
a	Before compression (mm)	241	241	279	279	
b	After compression (mm)	270	270	310	310	
v	Material	Ex. Al. Alloy	Ex. Al.	Ex. Al. Alloy	Ex. Al.	
vi	Weight of sleeve in (kg)	0.450	0.453	0.810	0.810	
vii	Breaking strength as percentage of UTS of conductor	95%				
viii	Conductivity as percentage of conductivity of conductor	100% of equivalent length of conductor				
ix	Resistance as percentage of measured resistance of equivalent length of conductor	Not more than 75% of equivalent length of conductors				

SCHEDULE OF QUANTITY (Appendix-I)

	Description	Unit	Quantity	Desired	Destination
				Delivery	
	(1.1) 90KN Single Suspension	Sets	4744	Within	Any store/
	(AGS Type) H/W fitting			Three	Site of
Hard Ware	including armour rod for ACSR			months	OPTCL
Fittings	Panther conductor			from the	within the
for ACSR	(1.2) 90KN Double Suspension	Sets	582	date of	State of
Panther	(AGS Type) H/W fitting			issue of	Odisha (will
(30+7/3.0	including armour rod for ACSR			P.O.	be indicated
0mm)	Panther conductor				in the D.I)
	(1.3) 120KN Single Tension	Sets	3128		
	H/W fitting for ACSR Panther				
	conductor				
	(1.4) 120KN Double Tension	Sets	1172		
	H/W fitting for ACSR Panther				
	conductor				

Hard Ware Fittings for ACSR	(1.5) 120KN Single Suspension H/W fitting including armour rod (AGS Type) for ACSR Zebra	Sets	291	
Zebra (54+7/3.1 8mm)	conductor (1.6) 120KN Doule Suspension H/W fitting including armour rod (AGS Type) for ACSR Zebra	Sets	124	
	conductor			
	(1.7) 160KN Single Tension H/W fitting for ACSR Zebra conductor	Sets	1528	
	(1.8) 160KN Double Tension H/W fitting for ACSR Zebra conductor	Sets	392	
Hard Ware Fittings for ACSR Moose	(1.9) 120KN Single Suspension (AGS Type) H/W fitting including armour rod for ACSR Moose conductor	Sets	324	
(54+7/3.5 3mm)	(1.10) 160KN Single Tension H/W fitting for ACSR Moose conductor	Sets	583	
	(1.11) 160KN Double Tension H/W fitting for ACSR Moose conductor	Sets	305	
Hard Ware Fittings for AAAC Zebra (37/4.0m	(1.12) 120KN Single Suspension H/W fitting including armour rod (AGS Type) for AAAC Zebra conductor	Sets	20	
m)	(1.13) 120KN Doule Suspension H/W fitting including armour rod (AGS Type) for AAAC Zebra conductor	Sets	98	
Hard Ware Fittings for AAAC Panther	(1.14) 90KN Single Suspension H/W fitting including armour rod (AGS Type) for AAAC Panther conductor	Sets	36	
	(1.15) 120KN Single Tension H/W fitting for AAAC Panther conductor	Sets	46	
Hard Ware Fittings for AAAC Moose	(1.16) 120KN Double Suspension (AGS Type) H/W fitting including armour rod for ACSR Moose conductor	Sets	16	
Hard Ware Fittings for	(1.17) Single Tension H/W fitting for Earth Wire	Sets	79	
Earthwire Vibrataion	(2.1) ACSR Panther conductor	Nos.	15022	
Damper	(2.2) AAAC Panther conductor	Nos.	262	
	(2.3) ACSR Moose conductor	Nos.	167	
Mid Span	(3.1) ACSR Zebra	Nos.	47	
Joint	(3.2) ACSR Panther	Nos.	947	
	(3.3) ACSR Moose	Nos.	29	
Repair Sleeve	(4.1) ACSR Panther	Nos.	275	

END OF TENDER SPECIFICATION